Scout Report sein out	2 To		The annual section of the section of
Noted in the NID File		ď	
Location map pinned			
Approval or Disapproval Letter			
Date Completed, P. & A. or operations suspended			
Pin changed on location map			
Affidavit and Record of A & P			
Water Shut-Off Test	4		
Gas-Oil Ratio Test	ر المراجعة		
Well Log Filed	and the same	<b>D</b>	
1 + 100		Latue SINA	

Shut-in status since 1975 (Previously Meagher #1)

Entered in NID File Entered On S R Sheet Location Map Pinned Card Indexed	Checked by Chief Copy N I D to Field Office Approval Letter Disapproval Letter
IWR for State or Fee Land	
COMPLETION DATA:  Date Well Completed 9/22/48  OW	Location Inspected  Bond rolassed  State of Fee Land
GW OS PA	FILED
Driller's Leg	GR Micro Micro

Rangely, Colorado

October 20, 1948

Equity Oil Company 401 Utah Oil Building Salt Lake City, Utah

Attention: Mr. V. B. Peterson

Subject: Core Analysis Results
Ashley Valley # 1 Well
Ashley Valley Field
Uintah County, Utah

### Gentlemen:

Diamond core #4 in the top of the Weber section of this well has been analyzed in our Rangely laboratory with the results herein submitted in graphical and tabular form.

Of the 16 feet represented in this core, 14 feet were found to be permeable and oil productive. An average horizontal permeability of 59.8 millidarcys in this permeable part gives a total productive capacity of 857 millidarcy feet. With sufficient driving force to move the oil to the well bore, this well should be a commercial producer.

We lack important data on reservoir conditions to make an accurate calculation of recoverable oil, but for estimation purposes we have assumed certain values for this unknown data and have made calculations as follows:

Case #1 (assuming a gas/oil ratio of 100 oubic feet per barrel, a viscosity of 2.5 centipoise, a formation volume factor of 1.10, and a saturation pressure of 1500 PSI):

Calculated Oil Recovery:

By Gas Expansion: 185 barrels per acre foot (to Zero PSI)
By Water Drive: 560 barrels per acre foot (to 100% Water Cut)

Case #2 (assuming gas/oil ratio of 200 cubic feet per barrel, a viscosity of 1.5 centipoise, a formation volume factor of 1.15, and a saturation pressure of 1750 PSI):

Calculated Oil Recovery:

By Gas Expansion: 203 barrels per acre foot (to Zero PSI)

By Water Drive: 527 barrels per acre foot (to 100% water cut)

Non-uniform water encroachment and economics of production will probably force abandonment of the well long before 100% water cut is obtained. Assuming that each significant sone is in contact with water moving laterally with sufficient velocity to overcome gravitational effects, water cut history is predicted as follows:

Oil Recovery	Water Cut, Percent		
Barrels per acre foot	Case #1	Case #2	
150	78	68	
200	85	78	
250	90	85	
<b>30</b> 0	98	90	

Rangely, Colorado

(2)

Equity Oil Company

Ashley Valley #1 Well (continued)

With more penetration of the formation and further information on reservoir conditions we can expect to give recovery figures and water fluid history predictions with more accuracy and more in detail.

We hope to be of service to you on future wells.

Yours very truly,

ilbert A. Parks

RESERVOIR ENGINEERING LABORATORIES

Rangely, Colorado

Equity Oil Company

Ashley Valley #1 Well (continued)

### VERTICAL PERMEABILITY TESTS

Sample	Depth	Vertical Permeability
Mumber	Feet	Millidarcys (Liquid)
1	4138.6	2.0
2	39.5	1.3
3	40.5	0.7
4	41.5	4.3
5	42.5	1.3
6	43.5	8.2
7	44.5	1.6
8	45.5	88.
9	46.5	61.
10	47.5	17.
11	48.5	168.
12	49.5	14.
13	50.5	21.
14	51.5	127.

### SUMMARY OF CORE ANALYSIS RESULTS

Formation Cored: Weber	Permeable Oil Productive Sand: 14 feet				
Depths Cored: 4136 - 4152 feet	Average Permeability (Horizontal): 59.8 millidarcys				
Subsea Depths: +780' to +764'	Total Productive Capacity: 837 millidarcy feet				
Core Recovery: 16 feet: 100%	Average Oil Saturation: 28.9 percent of pore space				
Average Porosity: 13.7 percent	Average Water Saturation: * 16.8 percent of pore space				

Calculated Oil Recovery: (see letter of transmittal)

<sup>\*</sup> Core samples were exposed several days to dry air before analysis was begun. This water saturation as found is low. In the calculations an average connate water saturation of 20.0 percent has been used (this value taken from average of all Weber section wells in the Rangely field for similar permeability)

Rangely, Colorado

### CORE ANALYSIS REPORT

Company		OIL CO					403		20 - 00						
Well	ASHLEY	VALLEY	#1		· · · · · · · · · · · · · · · · · · ·	_ Elev	ration 491	6' RT		Engine	ers <u>G</u>	Piki_			
Field	ASHLEY	VALLEY				_ Тур	e Core DIA	MOND C	ORE IN	MATER	BASE	MUD			
County	UINTAE		State	HATU			narksC	ORE #4	(4136'	-41521	)				
C001117			<b>U</b> .U.U					hility M	ld <b>o</b> c						
		· · · · · · · · · · · · · · · · · · ·					100 75	<b>5</b> 0	25		W	ater satu	ration,	% Por	re <b>@</b> -
Sample	Depth	Permeability	Porosity		Saturation Fore Space	Probable	Para	sity %			0	il saturat	ion, %	Pore	21111.
Number	Feet	Millidarcys	Percent	Oil	Water	Production	100 75	50	<b>25</b> 0	)		2,5			75
					Water	· .	11111111		<del>-11</del>		1				1
1		1 1		l	}		<b>┃</b> ┡┽┿┽┼╋┿┿	++++	<del>-</del> <del> - - - - - - - - - - - - - - - - - -</del>		1	<del>┞┼┼┼</del>	++++	++++	
į.				İ	İ		11++++++	╁┼╂┼┼	╁╂┼┼┼		}	+++++	++++	+++	<del>     </del>
]		i i		1		1		╁╁╂┼┼┥	╌┼╁┼┼┼┥		1	<del>                                      </del>	++++	+++	1+
1		į l						++++++				+++++	╁┼┼┼		+ + + +
1						ł		$\downarrow\downarrow\downarrow\downarrow\downarrow$	┵╁┼┼╢		İ	1	+++		11
	/				Į	ł			44444	•	4	<del></del>	++++	+++	+++-
1					<u> </u>					4136	<u> </u>	1:::::	$\Box$		11
					T						E	1	4444		1 1 1 1 1
1				ļ		1				ı	7		4-4-1		+
1	4138.6	0.3	5.0	38.0	28.0	011			2	•	<u> </u>	1111111	633		j   .
2	39.5	11.	12.2	25.5	18.9	011			<b>A</b>	4140	]:::::	777/20			
3	4140.5	2.1	13.6	34.0					مرا	2120	]		33		
4	41.5	29.	17.0	27.0					α (		1	2022			
	42.5	6.3	14.0	31.5					10			222	3		
		9.1	12.8	29.0			<u> </u>	<del>                                      </del>	ja Je			13.57.7	3		
0	43.5						<b>┃┠┼┼┼┼</b> ┼	++++	1111			11111	2/4	1111	1
7	44.5	0.6	9.0	36.7			▗▋ <del>▍╇┆┊</del> ┾╋╫	$+\pm\pm$		4145	1777	1377	741	<del>                                      </del>	
8	45.5	50.	13.2	22.0			<del>┃</del> ┢╅ <del>╽┼┼┞</del> ╇╪	++9+	· · · · · · · · · · · · · · · · · · ·			1	++++		-
9	46.5	173.	20.2	23.7								111111	4 + + +		
10	47.5	45.	12.9	28.8			┨ <del>╏╻┿┿</del> ┼┼	<del>       </del>			1	CKOK)	3		++
11	48.5	171.	14.9	28.2				<del></del>	444			· MAN	4	1	-+++
12	49.5	21.	15.3	31.6			<del>╺</del>	++++		4150	<b>∤</b> ∙. · · .	· MAN	7		
13	4150.5	178.	16.0	27.4				<del>↓</del> ↓ <b>↓</b> ↓,			1	MAN	•	1	
14	51.5	141.	16.2	21,7	14.2	011		4444			ļ	10000	++++		
					1			$\bot \downarrow \downarrow \downarrow \downarrow \downarrow$		4152				1 88	
	ļ	1				1		<u> </u>		TD.	1	8EPT	SMBER	194	9
	<u> </u>	İ		1		į .					4				444
		1		1							1		444		
	1	j		1							1			1	
		1		ł	ł	1					j				1
		1		1		1					i				Ш
	[									]	1				
								1111		<b>†</b>	1				
	ļ			1				1111	<del>                                      </del>	1	1				-   ! -
	İ		}			1		<del>                                      </del>	<del>                                     </del>	1	1				
	l	1	İ	l		1	<u>▋</u> ┡ <del>┞</del> ┼┼┼┼┼┼	<del>             </del>	<del>                                      </del>		ļ	<b>-</b>	++++	<b>†</b> † † †	111
	1			j		Ì	<b>I</b>	┼┼╂┼┼	<del>┞</del> ┼╂┼┼┼┼	1	i			1:11	11
		1	1			1	I <del>                                     </del>	<del>-                                     </del>	+++++	†	1	<u> </u>		<del>         </del>	++++
	1	1		l		1	$I \rightarrow + + + + + + + + + + + + + + + + + + $	╁┼╂┼┼	┼┼╂┼┼┼┼	i		1++++	++++	++++	
	]		1	1		1	<del>┇┋╅╅┿╅╂</del> ┼	<del>-                                     </del>	╅╀╃┼┼┼	1	1	111111	++++	<del>                                     </del>	++++
	1		1	1		1	<b>╻╻┼┼┼┼┼</b>	++++	<del>╽</del> ┼╂┼┼┼┼	· ·		┠┼┼┼┼	++++	+++	++++
				1			╻╻┼┼┼┼┼	╌┼╂┼┼	<del>┼╎╏╎┆</del> ┼┼	-	1	1	++++	++++	
			1			1				ļ	1		+++	1:11	444
		1	1	1						1			$\coprod$	1111	-1
						1				]	1		ЩЦ		1111
					1	1				1	1				
			İ	1		1					1		ШП		
	1	1		1	1					1	ļ			$\Pi\Pi$	

# STATE OF UTAH OIL & GAS CONSERVATION COMMISSION

SALT LAKE CITY, UTAH

Fee and Patented
State
Lease No
Public Domain
Lease No
Indian
Loone No

LAND:

otice of Intention to Drill			Subsequent Report of Wat	er Shut-off
otice of Intention to Change Plans			Subsequent Report of Alter	ring Casing
stice of Intention to Change Hans		1 18	Subsequent Report of Redi	rilling or Repair
tice of Intention to Red in or Repair	ino	1 1	Supplementary Well Histor	ry
otice of Intention to Abandon Well				
Deepen Well.				
			E OF REPORT, NOTICE, OR OTHER DATA)	
			November 16.	<b>, 19</b> <u>59</u>
7ell No1 is located26	665 ft. from			
Nw 1/4 SW 1/4 (1/4 Sec. and Sec. No.)	5S		22E	SL
(1/4 Sec. and Sec. No.)	(Twp.)		(Range)	(Meridian)
Ashley Valley	Uiı	ntah		Utah
(Field)	(Co	unty or	Subdivision)	(State or Territory)
drilling and plugging bond has been tate names of and expected depths to objects, cementing points, and all other import	n filed with .  DETA  ective sands; sl tant work, surf	ILS (how si	OF WORK  izes, weights, and lengths of pro ormation, and date anticipate sp	pposed casings; indicate muddir pudding-in.)
drilling and plugging bond has been state names of and expected depths to objects, cementing points, and all other import Old total depth 4152. It sand-frac new hole section, pro-	DETA  ective sands; sl tant work, surf  Plan to ki  roduce Web	ILS (how siface for	OF WORK  izes, weights, and lengths of pro ormation, and date anticipate sp e11, take two 50-foot  nd Phosphoria. Presen	oposed casings; indicate muddingudding-in.)  cores of Weber section  t Weber penetration i
The elevation of the derrick floor about the derrick floor about drilling and plugging bond has been state names of and expected depths to objects, cementing points, and all other important to total depth 4152. It sand-frac new hole section, proportionly 16. General practice is	DETA  ective sands; sl tant work, surf  Plan to ki  roduce Web	ILS (how siface for	OF WORK  izes, weights, and lengths of pro ormation, and date anticipate sp e11, take two 50-foot  nd Phosphoria. Presen	oposed casings; indicate muddingudding-in.)  cores of Weber section  t Weber penetration i
drilling and plugging bond has been State names of and expected depths to objects, cementing points, and all other import Old total depth 4152°. It sand-frac new hole section, proportionly 16°. General practice is	DETA  cetive sands; sl tant work, surf  Plan to ki  roduce Webe  s to produce	ILS (how siface for	OF WORK  izes, weights, and lengths of pro ormation, and date anticipate sp e11, take two 50-foot  nd Phosphoria. Presen	oposed casings; indicate muddingudding-in.)  cores of Weber section  t Weber penetration i
State names of and expected depths to objects, cementing points, and all other import Old total depth 4152°. It sand-frac new hole section, property 16°. General practice is	DETA  cetive sands; sl tant work, surf  Plan to ki  roduce Webe  s to produce	ILS (how siface for	OF WORK  izes, weights, and lengths of pro ormation, and date anticipate sp e11, take two 50-foot  nd Phosphoria. Presen	oposed casings; indicate muddingudding-in.)  cores of Weber section  t Weber penetration i
State names of and expected depths to objects, cementing points, and all other import Old total depth 4152°. It sand-frac new hole section, property 16°. General practice is	DETA  cetive sands; sl tant work, surf  Plan to ki  roduce Webe  s to produce	ILS (how siface for	OF WORK  izes, weights, and lengths of pro ormation, and date anticipate sp e11, take two 50-foot  nd Phosphoria. Presen	oposed casings; indicate muddingudding-in.)  cores of Weber section  t Weber penetration i
State names of and expected depths to objects, cementing points, and all other imports Old total depth 4152. It sand-frac new hole section, proportionly 16. General practice is one or the other is 100% water	DETAL ective sands; sl tant work, surf Plan to ki roduce Webe s to produce.	ILS (how siface for	OF WORK  izes, weights, and lengths of pro ormation, and date anticipate sp e11, take two 50-foot  nd Phosphoria. Present where and Phosphoria se	oposed casings; indicate muddingudding-in.)  cores of Weber section to Weber penetration in ection together unless
drilling and plugging bond has been state names of and expected depths to objects, cementing points, and all other import Old total depth 4152°. It sand-frac new hole section, proportionally 16°. General practice is one or the other is 100% water understand that this plan of work must remark the Old General	DETAL ective sands; sl tant work, surf Plan to ki roduce Webe s to produce.	ILS (how siface for all we can we will all in which all in which all in which all in we will all in which all in which all in we will all in which all in	OF WORK  izes, weights, and lengths of proormation, and date anticipate special, take two 50-foot  and Phosphoria. Presenteber and Phosphoria security	oposed casings; indicate mudding- pudding-in.)  cores of Weber section t Weber penetration in ection together unless re operations may be commenced
State names of and expected depths to objects, cementing points, and all other import Old total depth 4152. It sand-frac new hole section, pro-	DETAL ective sands; sl tant work, surf Plan to ki roduce Webe s to produce.	ILS (how siface for all we can we will all in which all in which all in which all in we will all in which all in which all in we will all in which all in	OF WORK  izes, weights, and lengths of proormation, and date anticipate special, take two 50-foot  and Phosphoria. Preserveber and Phosphoria security	oposed casings; indicate mudding pudding-in.)  cores of Weber section to Weber penetration in ection together unless are operations may be commenced.

forms to applicable rules, regulations and orders.

# **EQUITY OIL COMPANY**

806 UTAH OIL BUILDING SALT LAKE CITY 1. UTAH November 16, 1959

Oil & Gas Conservation Commission of the State of Utah 310 Newhouse Building Salt Lake City, Utah

### Gentlemen:

We enclose a Sundry Notice covering the opening of additional section in our Ashley Valley No. 1 well which is located in the Ashley Valley field, Uintah County, Utah. Also attached is a bond covering this company's operations in Ashley Valley.

If there are any further requirements, please advise.

Yours very truly,

EQUITY OIL COMPANY

C. E. Johnson

Production Engineer

CEJ/akc

Enclosures

### November 17, 1959

The Equity Oil Company 806 Utah Oil Building Salt Lake City, Utah

Attention: C. E. Johnson, Production Engineer

Gentlemen:

This is to acknowledge receipt of your notice of intention to deepen Well No. Fee 1, which is located 2665 feet from the north line and 725 feet from the west line of Section 23, Township 5 South, Range 22 East, SLBM, Uintah County, Utah.

Please be advised that approval is hereby granted.

Please take note that should it be necessary to plug and abandon said well you are hereby requested to give advance notice of the date and time said plugging will take place to one of the following named individuals, by phone or otherwise, in order that our petroleum engineer bay be present to inspect the manner in which the well is being plugged:

- H. G. HENDERSON, Petroleum Engineer:
  Office Phone: DA 24721, Ext. 438 or DA 8-0701
  Home Phone: DA 2-4496
- C. B. FEIGHT, Executive Secretary:

  Home Phone: HU 5-2721
  Office Phone: DA 2-4721, Ext. 438 or DA 8-0701

All other forms of communication should be addressed to the Oil & Gas Conservation Commission, 310 Newhouse Building, Salt Lake City, Utah.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FEIGHT EXECUTIVE SECRETARY

01		3	
01	i		
1			

# STATE OF UTAH OIL & GAS CONSERVATION COMMISSION SALT LAKE CITY, UTAH

Fee and Patented
State
Lease No
Public Domain
Lease No

Lease No. .....

SUNDRY NOTICES AND REPORTS ON WELLS

SOMBILL	TOTICES 1111	orthic orthogram	
N. dia a C. T. dan dia a da Daili		Subsequent Report of Wa	ater Shut-off
Notice of Intention to Drill Notice of Intention to Change Plant			ering Casing
Notice of Intention to Change 112		Subsequent Report of Re	drilling or Repair
Notice of Intention to Red in or Alt	er Casiny X	Supplementary Well Hist	ory
Notice of Intention to Abandon \			
		<u> </u>	
(INDIC	ATE ABOVE BY CHECK MARK NAT	JRE OF REPORT, NOTICE, OR OTHER DATA	)
		January 20	, 1960
Well No1 is locate	ed .2665 ft, from	line and <b>7.25</b> ft. from	${\bf A} \left\{ \begin{array}{c} {\bf Z} \\ {\bf W} \end{array} \right\}$ line of Sec23
NW 15W 2 Sec. 23 (1/4 Sec. and Sec. No.)	5S	22E	Salt Lake
Ashley Valley	Uinta		Utah (State or Territory)
(Field)	(County	or Subdivision)	(State or Letritory)
The elevation of the derrick flo	or above sea level is	4916 feet.	
A drilling and plugging bond ha	as been filed withQ	il & Gas ConserComm.	
	TOTAL IT C	OF WORK	
		OF WORK	di indicate mudding
(State names of and expected depths jobs, cementing points, and all other	to objective sands; show important work, surface	formation, and date anticipate s	spudding-in.)
		1.1 O.m. A f 41:52	11 42 42951 Ban 218
Old TD 4152', rigged	i nb wur briter in	bing. Cored from 4152	10 4265 . RMI 22
tubing setting packer at	4119 * (Bottom of	7" casing is at 4134°	- open hole 4134 - 4285
Casing perforated in Photo	bi. fommodiom	from 4004 - 41041) Di	enlaced mud with water
Casing periorated in Page	sphoria roduation	110m 4094 = 4104 / DI	spieced mud with water
and water with oil. Pres	ssured up below pa	cker - had communicati	on thru perforations
at 4094 - 4104*. Plan to	run and cement 5	", 15# J-55, flush joi	nt liner and selectively
C 1 1 to 1 to 1			
perforate and treat Weber	r iormation.		
I understand that this plan of work	must receive approval in	writing by the Commission befo	ore operations may be commenced.
•	• •		
Company Equity Oil Compa	any		
Address 806 Utah Oil Blo	ŧσ	D. Palan	ja-
Address ove otan oil bi	7.5.t	/ /	
Salt Lake City,	Utah	Title Production	Engineer

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.

1/

ol

### (SUBMIT IN DUPLICATE)

### STATE OF UTAH

# OIL & GAS CONSERVATION COMMISSION

SALT LAKE CITY, UTAH

Fee	and	Patented
Stat	е	

LAND:

State		•••••	
Lea	se	No.	•••••

Public Domain ......

# SUNDRY NOTICES AND REPORTS ON WELLS

Notice of Intention to Drill  Notice of Intention to Change Plans  Notice of Intention to Redrill or Repair  Notice of Intention to Pull or Alter Casing	Subsequent Report of Water Shut-off	x
Notice of Intention to Abandon Well	Supplementary with resolution	
		l

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

		Narch 8,	<u>19.60</u>
Well No1 is l	ocated 2665 ft. from $\begin{cases} 1 \\ 8 \end{cases}$	line and <b>725</b> ft. from	{ <b>₹</b>   W   line of Sec <b>23</b>
NW SW Sec. 23	58	22 E	Salt-Lake
(1/4 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)
Ashley Yalley (Field)	Uintah (County	or Subdivision)	(State or Territory)

The elevation of the derrick floor above sea level is .49.16..... feet.

A drilling and plugging bond has been filed with ... Cil & Gas Conservation Commission

### DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important work, surface formation, and date anticipate spudding-in.)

Ram 244.79° (less threads) of 5" OD, 15%, J55 Hydrill Flush Joint casing with Baker Whirler Shoe on bottom and Baker Texas Pattern Shoe on top. Total length of limer 247.20°. Cemented liner from 4038° to 4285° with 108 cu. ft. of slurry consisting of 30 sacks of regular cement, 30 cu. ft. of Posmix A, 1500% Gilsonite(at 25%/cu. ft.) 2 sacks of Gel (4% mix), 7½ gallons of water/cu. ft. Maximum pressure 1100%. Pulled loose and pulled up 496° shutting in for 24 hours. Pressured casing to 700%, took fluid, pumped in at 500%. Ram in with Halliburton RTTS packer & set at 3975°, pumped in at 4 BPM at 1250%. Mixed 5 sacks regular cement followed by 30 sacks regular cement with 10% Gilsonite/sack, followed by 40 sacks regular cement. Displaced with 21½ bbls water, maximum pressure 4250%, shut in w/3600%. Ram in with bit, top of cement at 3975°, drilled out to 4275°. Perforated W/McCullough Macjets, 4 SPF 4157 - 64, 4197 - 4207°, & 4244 - 54°. Set Halliburton RTTS packer at 4215°, fracced well thru tubing using 21,500 gal lease water, 1428% WG-4 Gelling agent, 666% CW-1 Breaker, 25600% 20-40 sand and 72 rubber-covered nylon balls. Maximum pressure 4600%. Understand that this plan of work must receive approval in writing by the Commission before operations was experied commenced.

Company Equity Cil Company	
	By EEStmoor
Address 806 Utah Oil Bldg.	By Colmon
Salt Lake City, Utah	Title Preduction Engineer
	- AVI

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.

ъV

Pulled packer and reran tubing w/221.85\* 2" J55 on bottom and 4016.59\* 2½"J55 on top, set at 4251.44\* RKB. Opened well to tanks 2/9/60, well flows approximately 55 bbls of eil and 1600 bbls of water per day.

harch u, w

1 2665 *y* 725

Ny 32 Sec. 23 Salt fake

Asidey Valley Uintah Utah

4910

Oil & cas Conservation Commission

Ran 244.79' (less threads) of 5" \*0, 15#, 355 hydrill blush Joint casing with maker whirler Shoe on bottom and Baker Temus Pattern Shoe on top. Total length of liner 247.20'. Chaented liner from 4080' to 4285' with lot cu. it. of slurry consisting of 30 sacks of regular coment, 30 cu. it. of Posmix A, 1500% Gilsonite(at 25m/cu. 1t.) 3 sacks of vel (45 mid.), 7g gallons of water/cu. ft. Maximum pressure 1100%. Pulled lower and pulled up 490' shutting in for 24 hours. Tressured casing to 700%, took fluid, pumped in at 500%. Ran in with halliburten PTS packer & set at 2973', pumped in at 4 MPM at 1250%. Fixed 5 sacks regular coment with 10% Gilsonite/sack, 101'owed by 40 sacks regular cenert. Lispleces with coment with 10% Gilsonite/sack, 101'owed by 40 sacks regular cenert. Lispleces with cenert at 5973', drilled out to 4275'. Perferated w/200%. Ran in with hit, top of cenert at 5973', drilled out to 4275'. Perferated w/200% and aciets of 895.

4157 - e4, 4197 - 4207', a -254 - 34'. Set halliburdon 2178 packer at 4310', fracced well thru tubing using 21,500 gal lease water, 1428C 2-4 Celling agent, edge C-1 breeker, 25000% 2 -45 send and 72 rubber-covered nylon balts. Maximum pressure 46.80.

Equity Oil Company

Set t late City, Tellithin

Production Encineer

x

COMMISSIONERS

C. S. THOMSON

C. R. HENDERSON

M. V. HATCH

J. H. REESE

D. M. DRAPER

EXECUTIVE DIRECTOR

C. B. FEIGHT



PETROLEUM ENGINEERS
PAUL W. BURCHELL
CHIEF ENGINEER

### THE STATE OF UTAH

### OIL & GAS CONSERVATION COMMISSION

348 EAST SOUTH TEMPLE SUITE 301 SALT LAKE CITY, UTAH 84111

DAvis 8-5771

March 30, 1966

Equity Oil Company 806 American Oil Building Salt Lake City, Utah

Ashley Valley Field

Meagher #1

O SW NW Sec. 23, T. 5 S., R. 22 E.,

Uintah County, Utah

#### Gentlemen:

Upon checking our files we find that we do not have a driller's log and electric and/or radioactivity logs for the above mentioned well(s). It was also noted that we have very little information on said well(s). This well(s) was drilled prior to the establishment of the Commission, however, we are making an attempt to complete our records on wells that have been drilled in the state.

It would be appreciated if you could forward said information and logs to this office at your convenience.

Thank you for your assistance in this request.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

ANNETTE R. HANSEN RECORDS CLERK

Carrier Al Hanson

arh

9

M

# **EQUITY OIL COMPANY**

806 AMERICAN OIL BUILDING SALT LAKE CITY, UTAH 84101 April 13, 1966

Re: Ashley Valley Field

Meagher #1

C SW NW, Sec. 23, T 5 S., R. 22 E.,

Uintah County, Utah

Oil & Gas Conservation Commission of the State of Utah Suite 301 348 East South Temple Salt Lake City, Utah 84111

Attention: Annette R. Hansen, Records Clerk

Gentlemen:

In reply to your letter of March 30, 1966 bearing the above subject, enclosed is the Well Completion Report and Electric Log you requested.

Very truly yours,

EQUITY OIL COMPANY

A. K. Clayton

Assistant Secretary

AKC/jf

Enclosure

DGCC-3



n UGCC-3	<u>.</u>	STATE	DE UTAH ,	SUBMIT II	See other in		
	OIL & GA	S CONSERV			structions of reverse side	5. LEASE DESI	IGNATION AND SERIAL NO.
WELL CON	API FTION	OR RECON	APLETION R	EPORT AN	ND LOG*	6. IF INDIAN,	ALLOTTEE OR TRIBE NAME
TYPE OF WELL				Other		7. UNIT AGREE	EMENT NAME
b. TYPE OF COMP	WORK DE	EP- PLUG	DIFF.	Other		S. FARM OR L	4
WELL X	OVER L EN	DACK (	heath.	other		- <del>1</del> 461	mer ree
	Equity Oi	1 Company				9. WELL NO.	44
. ADDRESS OF OPER		- 011 D14	Cald To	ta City II	+ah		POOL, OR WILDCAT Web
LOCATION OF WEL	806 Amera	can Oil Bld	ccordance with an	y State requireme	nts)*	Ash le	v Vallev
At surface 2	665 * FNL	& 725 FWL	-Sec. 23 <del>,⊶5</del> 5	-22E		11. SEC., T., R. OR AREA	., M., OR BLOCK AND SURVEY
At top prod. inte	rval reported b	elow 🔢 👸		Signal Control of the		Section	1 23
At total depth		ے ک		ີ ວຸ ລ້ຳ		T 5S,	R 22B
			14. PERMIT NO.	DATI	E ISSUED	12. COUNTY OF	R 13. STATE
					<del></del>		19. ELEV. CASINGHEAD
DATE SPUDDED	16. DATE T.D. 9/21/4		E COMPL. (Ready to /22/48	p prod.)   18. EL	EVATIONS (DF, REE 4916 DF	, RT, GR, ETC.)*	10. 2021. 000
. TOTAL DEPTH, MD		UG, BACK T.D., MD &	TVD   22. IF MUL	TIPLE COMPL.,	23. INTERVALS		S CABLE TOOLS
4152 DF			ноw м			04152	
. PRODUCING INTER	VAL(S), OF THIS	S COMPLETION—TOP	, BOTTOM, NAME (M	ID AND TVD)*			25. WAS DIRECTIONAL SURVEY MADE
4134 -	4152		Ž				
. TYPE ELECTRIC A	ND OTHER LOGS	RUN					27. WAS WELL CORED
Sch1	umberger	Electric Lo					Yes-Btm 85°
3.			NG RECORD (Rep	ort all strings set	(in well)	G RECORD	AMOUNT PULLED
CASING SIZE	WEIGHT, LB			EE 51211	75 Sac		
16" 10-3/4"	32.7	75# 50		120	235 Sac		
7"	20 & 23			)11	300 Sac	ks	
	<u> </u>	LINER RECORD	<u>역 및</u> 경 (4	1	30.	TUBING RECO	RD
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MI	
- 5122	101 (110)		: -		21/2"	4142 *	
				<u> </u>		COLUMN COMPANY	SOUTE TO
1. PERFORATION REC	CORD (Interval,	size ana number)	73 1 ***	32. A	ACID, SHOT, FRA		D OF MATERIAL USED
			پ. ن				
			·				
			PRO	DUCTION			
3.* ATE FIRST PRODUCT	ION PRO	DUCTION METHOD (	;		type of pump)		STATUS (Producing or t-in)
9/22/48		F1ow	106				Preducing
ATE OF TEST	HOURS TESTE		PROD'N, FOR TEST PERIOD	оіц—вя́ц.	GAS-MCF.	WATER-BBL	. GAS-OIL RATIO
9/22/64 LOW. TUBING PRESS.	12 He		OIL—BBL.	GAS-MCI	F. WATE	CR—BBL.	OIL GRAVITY-API (CORR.)
ECT A CHARTY EMERGE		24-HOUR RAT					
34. DISPOSITION OF G	AS (Sold, used f	or fuel, vented, etc.		······································		TEST WITNES	SED BY
5. LIST OF ATTACH	MENTS			,		<u> </u>	
6. I hereby certify	that the foreg	oing and attached i	nformation is com	plete and correct	as determined from	m all available r	ecords
36. I hereby certify		oing and attached i	nformation is com	plete and correct	as determined fro		ecords

# NSTRUCTIONS

Hem 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Hems 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional atta pertinent to such interval.

Hem 29: "Sacks Gement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Hem 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

7

.

Hole was deepened to 4285° in 1960 and you already have a supplemental Well History on this.  Hole was deepened to 4285° in 1960 and you already have a supplemental Well History on this.  Supplemental Well Hist	FORMATION	TOP	BOTTOM	DESCRIPTION, CONTRINTS, ETC.	`	TOP	P
#430		7617	5.5			MEAS. DEPTH	TRUB VERT. DEPTH
Hole was deepened to 4285° in 1960 and you already have supplemental Well History on this.  Supplemental Well History on this.  Butrada, 1074 + 384  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1074 + 287  Butrada, 1077  B	eper	77	413c +		,	069	+ 4226
Hole was deepened to 4285* in 1960 and you already have supplemental Well History on this.  Supplemental Well History on this.  Carmel 2300 4-256  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 2300 4-261  Carmel 3300 4-261	sa.					1013	+ 3886
Hole was deepened to 4285° in 1960 and you already have supplemental Well History on this.  Supplemental Well History on this.  Supplemental Well History on this.  Carmel School +287  Ca						1074	+ 3842
supplemental Well History on this.  Supplemental Well History on t		Hole was	deepened to	in 1960 and	<u>.</u> £	2046	+ 2870
Nave   1970			Well H	en this.	R.	2300	+2616
Second   S					. 0	2400	+ 2516
Moentepi				8 <b>2,</b>		3125	+ 1791
### ### #### #### #### #### #### #### ####				***		33067	+ 1610
Meber Promitive with Country 138 138 138 138 138 138 138 138 138 138		٠.					+ 926
Equition (1.5)  Solve to the control of the control		i, (°					+ 780
A Company of the Comp		•		· · · · · · · · · · · · · · · · · · ·			
A CAN CAN CAN CAN CAN CAN CAN CAN CAN CA		8		<b>3</b> (2)			
Accordance of the second secon		III.				\$ .	
Service of the property of the		)		7		<u> </u>	
tinga tanas tanas tanas original		÷.				Υj	
		ĺ		\$38 \$1		î <u>t</u> i	
				:"(:		<u>10:</u>	
2010 - 6011 - 6011 - 77	<b>S</b>					1	
	1,	(I)		try		X	
	4 1	/ (S		5.1 (*)			

# INSTRUCTIONS

\* General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be outputted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not field prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Hem 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State

or Federal office for specific instructions.

Hem 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Hems 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing intervals, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified.

interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval.

Item 29: "Sacks Coment": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

4136 4152 - TD Sandstone  Hole was deepened to 4285° in 1960 and you already have supplemental Well History on this.	Prontier Dakota Morrison Bntrada Carael Navajo Chinle Moenkopi Phosphoria Weber	2046 2300 2400 3125 33067 4136	TRUB VBRT. DBFTH + 4226 + 3886 + 3842 + 2870 +2616 + 2516 + 1791 + 1610 + 926 + 780
4152 - TD Sandstone as deepened to 4285° in 1960 and you alremental Well History on this.	Prontier Dakota Morrison Bntrada Carael Navajo Chinle Moenkopi Phosphoria		+ 4226 + 3886 + 3842 + 2870 +2616 + 2516 + 1791 + 1610 + 926 + 780
4152 - TD Sandstone as deepened to 4285° in 1960 and you alr emental Well History on this.	Prontier Dakota Morrison Bntrada Carael Navajo Chinle Moenkopi Phosphoria	690 1013 1074 2046 2300 2400 3125 33067 4136	+ 4226 + 3886 + 3842 + 2870 + 2616 + 1791 + 1610 + 926 + 780
as deepened to 4285° in 1960 and you alremental Well History on this.	Dakota Morrison Butrada Carael Navajo Chinle Moenkopi Phosphoria	1013 1074 2046 2300 2400 3125 33067 4136	+ 3886 + 3842 + 2870 +2616 + 2516 + 1791 + 1610 + 926 + 780
emental Well History on this.	Morrison Butrada Carael Navajo Chinle Moenkopi Phosphoria	1074 2046 2300 2400 3125 33067 4136	+ 3842 + 2870 +2616 + 2516 + 1791 + 1610 + 926 + 780
as deepened to 4285° in 1960 and you alremental Well History on this.	Entrada Carael Navajo Chinle Moenkopi Phosphoria Weber	2046 2300 2400 3125 33067 4136	+ 2870 +2616 + 2516 + 1791 + 1610 + 926 + 780
emental Well History on this.	Carsel Navajo Chinle Moenkopi Phosphoria	2300 2400 3125 33067 4136	+2616 + 2516 + 1791 + 1610 + 926 + 780
emental Well History on this.	io a prima	2400 3125 33067 3990 4136	+ 2516 + 1791 + 1610 + 926 + 780
	oria -	3125 33067 3990 4136	+ 1791 + 1610 + 926 + 780
	oria	33067 3990 4136	+ 1610 + 926 + 780
	<b>d</b>	3990	+ 926
	· · · · · · · · · · · · · · · · · · ·	4136	180
			•
			Blev. 4916

### Form DOGC-4

# GAS, & MINING

# STATE OF UTAH

### **DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL & GAS CONSERVATION**

1588 WEST NORTH TEMPLE SALT LAKE CITY, UTAH 84116 328-5771

State Lease No	
Federal Lease No	o. <u>.</u>
Indian Lease No.	·
Fee & Pat	X


REPORT OF OPERATIONS AND WELL STATUS REPORT


Agent	's Add	ress			806, 1 Lake Ci			<b>South</b> Co <b>84101</b> Sign	ompar gned	······································	06	2. Qu	y 011 Company
Phone	No			BO1-52	1-3515			Ti	tle		<i>7</i>		2
nd 4	Twp.	Range	Well No.	Days Produced	Barrels of	011	Gravity	Cu. Ft. of		Gallons of Gasoline Recovered	Water	(if	REMARKS (If drilling, depth; if shut down, cause; date and result of test for gasoline content of gas)
ec. 2	X	#S	22		9.22	0	1	1.3	Ni	. N	11	Ni	1 Shut In 51702 19
lec.	23		256	2	31	13	15		*			25	2,885
ec.2 W Se	3			3		7	22		*		•	13	8,778
ec.2 W Se	_			4	•	6	82		•		••	13	1,068
ec.2 E SE	2			5 <b>4</b>	*	19	24		•		*	29	2,976
ec.2 E ne		-	·	6	0	þ			•		•	0	Well shut in
ec.2 E NW	3			7	31	15	63		•		*	8	,187
ec.2	3			8	0	0			*		•	0	Well shut in
ec.2	•			9	0	0			•		•	0	Well shut in
ec.2 W SW	•			10	o	0 580	6 *		•		ē	23,0	Well shut in
													*Estimated
						ŀ							

GAS: (MCF) Sold	OIL or CONDENSATE: (To be reported On hand at beginning of month	in Barrels). 78
Flared/Vented Used On/Off Lease	Produced during monthSold during month	<del>ፍ</del> ዋልጽ :-ልኝ
	Unavoidably lost	
	Reason:	
	On hand at end of month	904.81

DRILLING/PRODUCING WELLS: This report must be filed on or before the sixteenth day of the succeeding month following production for each well. Where a well is temporarily shut-in, a negative report must be filed. THIS REPORT MUST BE FILED IN DUPLICATE.

# CONDENSED CORE ANALYSIS GRAPH





RZZE

# Cor Analysis Service

WELL Ashley Valley No. 1

DATE Nov. 24, 1959

**************************************	PERMEABILITY, MD.XX	% WATER XX	DEPTH AMD	PHYSI PROPE	1	FLU SATUR/		CORI
### ### ##############################	% POROSITY	% OIL	Bi 1					RECOR
### ### ### ### ### ### ### ### ### ##	20			<b>3</b> 5	11.2	35	28	-
### ### ### ### #### #################	· · <del>·                                  </del>							
### ### ### ### #### #################							markanin (m. 1988). Samuel de semblem de semblem de	-
### ### ### ### #### #### #### ########								N.R
Sub. Rd bb Sub.   105   12.3   44   34     Sub. Rd bb Sub.   33   12.3   44   34     Sub. Rd bb Sub.   65   14.1   24   31     Sub. Rd Bra. DAL Sub.   65   14.1   24   31     Sub. Rd Bra. DAL Sub.   90   11.6   39   36     DALFF Rd			4200		+		Margin and the decimination of the second	~-i
Sub. Rd bb Sub.   105   12.3   44   34     Sub. Rd bb Sub.   33   12.3   44   34     Sub. Rd bb Sub.   65   14.1   24   31     Sub. Rd Bra. DAL Sub.   65   14.1   24   31     Sub. Rd Bra. DAL Sub.   90   11.6   39   36     DALFF Rd		APOT-OF BLB BJG						1
In	<b>╌┼┼┼┼┼┼┼┼┼┼┼┼┼┼</b>		::::::	<b>1</b> 05	12.3	44_		-
Swein Brin, bill, stur.   900   11.65   30   36								
Diff. Rpi.   150   11.8   33   31   12   12   12   12   12   12								_
						<u> </u>		-1
					+			
Chitd.   Path   Path   A210   16   10.2   29   17	<sub>╸┡</sub> <del>╏╏╏╏</del> ╏				<del></del>	34		
Sun	┶╃╀┼┼┼┼┼┼┼┼┼		4210					
1209-13   Th. Let	<del>╴</del> <del>┊╏╏╏</del> ╏			<u> </u>			<u> </u>	Cor
				•			<del></del>	No.
### ### #### #########################				-	4			- 400
1.07   11.7   85   TR   420   421   420   421   420   421   420   421   420   421   420   421   420   421   420   421   420   422   421   420   422   421   420   422   421   420   422   421   420   422   421   420   422   422   422   423   422   423	<i>╸</i> <del>┊</del> ╅╂╂╂╂╂╂╂╂╂╂╂┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼					1	7	— to
### ### ### ### ### ### ### ### ### ##	<del>╸</del> <del>┥</del> <del>┩</del> ╅ <del>╏</del> ┼┼┼┼┼┼┼┼┼┼┼┼┼┼┼			-	11.7			426
	<del></del>			*		<del></del>		Rec
Petri   Strks   2.7   12.0   2.2   2.4   7.6   2.4   1.9   1.1   1.1   1.2   1.8   1.2   1.8   1.3	*++++++++++	S.S. V.P.G. W.BA.						μισυ <b>.</b>
Scat.   Patent   A220   2.4   7.0   37   19		Perm Strks.	-	_				
18   12.1   24   18   18   18   18   19   19   19   19			4220.					
Frii. Good Sort. 1.30 7.0 45 19 Ev. Ii. Brn. C11 St. 44 12.9 42 38  4221-22 G.R. V.F.G. 2.7 9.9 36 18  Arg. Si.y. S.S. 6.3 9.7 44 39  Oct. 9eat. Sts. 6.8 10.2 47 53  A222-23 B.B. 6. 11.1 45 34  F.G. Ev. Bort. 13.5 10.7 57 9  Frii. I. Brn. 14270 7.8 13.2 52 28  Odil Sts. 8 12.8 37 34  V.R.G. 11 Fart. 35 13.5 46 32  V.R.G. 11 Fart. 35 32 12.3 64 10  Lt. Brn. D11 Str. 2.7 11.4 79 20  Lt. Brn. D11 Str. 2.7 11.4 79 20  Lt. Brn. D11 Str. 2.7 11.4 79 20  Lt. Brn. D11 Str. 2.7 11.4 79 20  Lt. Brn. D11 Str. 2.7 11.4 79 20  Lt. Brn. D11 Str. 2.7 11.4 79 20  O.30 9.9 52 18  O.97 11.5 69 0	·		1	18			18	
Ev. 11. Brn. C11 3. 44 12.9 42 38  4221-22 G.R. W.F.G. 2.7 9.9 36 18  Arg. 31.v. S.S. 6.3 9.7 44 39  Occ. Sest. Stm. 6.8 10.2 47 53  A222-23 8.S. 6.3 11.1 45 34  F.G. Ev. Sort. 13.5 10.7 57 9  Fri. 1t. Brn. 4270 7.8 13.2 52 28  Oil Sin. 8. 12.8 37 34  V.E.G. In Fart. 33 13.5 46 32  V.E.G. In Fart. 33 13.5 46 32  V.E.G. In Fart. 22 12.1 47 30  Ferm. Strks W. 32 12.3 64 10  Ferm. Strks W. 33 13.5 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D11 Stn. 2.7 11.4 79 20  III. 37. D12 Stn. 35. D13 57 18  O.30 9.9 52 18	<u>╶┊</u> ╀┼┼┼┼┼┼┼┼┼┼┼┼┼┼			-				
	<del>┊</del> ┊╇╂┼╂╂╂╂╂┼┼┼┼┼┼	Ev. It. Brn. Q11						
		4221-22 G-R- M-H-C					<del></del>	
				6-8			53	
Fig. 1. Sort. 13.5 10.7 57 9 0.45 90 8 90 8 90 8 90 90 90 90 90 90 90 90 90 90 90 90 90	<u> </u>						34	
Fril   1.t   Bon   42.30   7.8   13.2   52   28	<del>┊╏┇</del> ┩	Fig. 12. Boldt.		13.5	10.7		9	
Oil 8th         32 J2.8       37 34         33 13.5       46 32         V.i. 6 in Farti       22 12.1       47 30         3.2 12.3       64 10         2.7 11.4 79 20         1.10 11.3 57 18         1.10 11.3 57 18         0.30 9.9 52 18         0.97 11.5 69 0	<del>┊</del> ╇╃┼┼┼╂ <del>┩┋</del> ╂┼┼┼┼┼┼┼	Pril 11 Blon.	2030				1 - 8 -	
7. 1. 6       1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	<del>****</del>	ON 3 8 4 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				_		
		122342718.8						
3.2       12.3       64       10         2.7       11.4       79       20         1.10       11.3       57       18         0.30       9.9       52       18         0.97       11.5       69       0			+					
1.10     11.3     57     18       0.30     9.9     52     18       0.97     11.5     69     0	<del>-</del>	Parm Rt Note W	† <b> </b>  :::::			64	10	
1.10   11.3   57   18   18   19   19   19   19   19   19		+ 12 34 1 541		2.7	Andreas - Control of the last			_
0.97 11.5 69 0		1227-30 L. Gr.						
	¢ ( 1 2 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		+					
and a resource and a substitution of the contract of the contr		Published (BL)	4240	-			0	

# Co Analysis Service

Ashley Valley No. 1
Nov. 26, 1959

PHYSICAL. FLUID RMEABILITY, MD . X----X CORE PROPERTIES SATURATIONS RECOPE % POROSITY 4240 16 12.5 4230-35 8.8. 39 35 V.F. d.I.E. Gr. 4.0 12.3 44 36 Hd. & Tite W/ 7.4 34 23 11.7 Strug of Perm. 18.0 11.5 34 36 B.S. W/Lt. Brn. 38 46 17.0 33 38 38 onl Stn. 27 13.8 4235-38 \$LB. V.P.G 13.5 12.0 42 42 Sitty. Well Cmtd 35 41 33 12.7 Pried. Hd. & Title 10 12.2 36 40 1.9 10.7 28 Scat 011 Sth. 8 **3**3 43 10.6 V.d. dood bil str 15 11.0 41 30 Fair Pern 15 9.4 38 44 44 49 12.7 35 14 46 35 10.9 2.4 61 B.S. Ang. 10.7 0.15 8.5 61 0.30 9.2 61 TR - N.R. \_4260\_ 5.7 59 0\_\_\_ 7.2 54 Core 0.85 9.8 59\_ No. 3 4260 To .4270 42851 0.20 9.5 55 Rec. 65 1.0 10.8 :::::: 74 :::::: 0.77 10.9 4.5 12.3 55 :::::: 4280 N.R. N.R. T.D.

Co Analysis Service Company Equity Oil Co. WELL Ashley Valley No. 1 Nov. 24, 1959

,				ATE.	Nov. 24,	1959	
PERMEABLET C. MO . XX	% WATER X	Na Ji Ni v	PHYSIC PROPER		TEL SATUR		and the second s
G POROSITY	7 30 (67 ) 5€ O(L	C.4	THE PART A	ment of the sale	THE STATE OF THE S	* * ( * # 70°) 	1
		M # -	MILITY MOL	ermanechastra i	W. C. T. T. C.	1.00	( <u>+</u> ( <u>+</u> , +
The state of the s		<i>4</i> 1 0		i			
			t :			1 manual control	
			83	14.8	30	30	
			170	13.5	29	32	
			13.0	9.9	46	23	
			29	11.7	42	25	
			31	12.7	43	47	
			200	ୂ13ୁ•ଃ :	42	30	
	4151-54 GR.		250	14.8	50	<sub>_</sub> 26	
· 🚭 · Li · · · · · · · · · · · · · · · · ·	Oil Stn. & Flour.		145	14.2	45	28	Core
	Fg Mg. S.S.	7,70	420	15.3	42	31	No.
	Good Sorting,		<u> </u>	14.1	.52	34	(Dee enin
	Sub. Rd. Sm.		290	14.5	43	33	er.in
	Vert. Frec.		_58	[11.3]	, 38	42	4151
	<b>3</b>  58+		72	15.0	30	28	to
	<del></del>		29	15.3	29	31	4200
			19	12.2	32	34	Rec.
		::::::	6	11.4	35	.37	1.000
	4164-76 Arg.		8.5	11.3	33	37	
	Fg. \$. \$. Grading		19	10.3	46	39	
	To V.F.G. Dola.	/17c -	6.3	11.3	35	33	
▋┼┼┼┼┼┼┼┼┼	Mty. in Part		<u>8.5</u>	11.6	32	25	
<b>▊</b> ╆╂╄╇╈┼╅╃╬╬╬╬╬╬╬╬	Scat. to Hvy.		11.5	9.8	49	39	
<b>▊</b> ┾╃┾╄╁╁┼┼┼┼┼┼┼┼	Pyritic.		17 8	10.2	49	37	
			44	13.3	33	31	
		-		12.1	41 70	41	
<b>╗</b> ┼┼┼┼┼┼┼ <del>┼</del> ┼┼┼┼┼┼┼┼┼┼	4176-80 Lt. gr.		27 0 0	13.9	<u> ३</u> ८ 	.38 .0	
	limey S.B.		0	6 5	38		
	limey S.B. Hd. & Title.		0	6.5		٥	
			Ö	5.4	45 45	ώι <del>ω</del> Ο	
		41°C -	0	7.0 5.4 8.9	63	G	
			0 0 0 1.07 0 0 0 0	?•7 ?•5	48 45 63 39 39 62	0 TR 9 13	
			0	7.5	39	2 <b>7</b>	
			0	7.5	62	27 0 11	•
			0	າ 8.9 !	28	17	
	4180-96 Gr.	:::::	0	6.0	37	0	
	S.S. F.G. &		0	6.2 _7.7	40	13	
	4180-96 Gr. S.S. F.G. & V.T.G. W Dollo. Mtx in Part	:::::	1.75	9.5	36	13	
	Mtx in Part		0	8.4		15	
	HOUGHT UK.	17.70	9	?.4 9.8	39 36	31	
	brn. 011 stn.		10	0.0 17.6 10.6 11.6	33	25	
			24	17.6	. 33 25	32	1
			11	10.6	28	38	
			10 24 11 12.5 19		38	32 38 36	,
			19	11	32	36	1

# HALLIBURTON

# FILACTURING SERVICE TREALING REPORT

Halliburton District Vernal Stage No. Halliburton Division Denver Page No.

COMPANY Halliburton	Division Deliver rage 10.
Field Ashley Valley Sec. 23 Twp.53 Rng	. 22E County Uintah State Utah
	NISHED BY THE WELL OWNER OR HIS AGENT:
Date Completed 1948 Formation Weber	Prev. Treat: Date_NoneType
Casing: OD /" Wt. 20-23 Depth 4038	Fluid: GalSand: Lb
Liner: OD 5th From 4038 To 4249	Pres. Treat: Interval: From 4148 To 4212
Perf.: From 4148-48 To 4151-55 Shots/Ft. 4	Tubing: Size 2-23 TEUE Depth 4127
Perf.: From 4158-65 To 4189-97 Shots/Ft. 4	Packer: Type RTTS&RBP Set at 4174
Perf.: From 4202- To 4212 Shots/Ft. 4	Max. Allowable Pres.: PSI: Tubing 3500 Casing 1000
Open Hole: Size None From To	Treat Thru: Tubing 🖾 Annulus 🔲 Casing i 🔲 Tubing/Annulus 🗋
MATERIALS USED	TREATMENT SUMMARY
Type JobSandoil	Trucks (No. and Type) TWO DT10'S
Fluid Weber crude 24,000 Gal.	Hyd. HP Available 1000 Used 700
Fluid Source Ashley Valley Lease	Pumps On Tubing 4-T10's Casing Manifold
API Gravity. 32 Viscosity. 10 CPS @ °F	AVERAGE RATES - BPM 7 0 7 5
Sand: Grade_20-40tb_24,000Sack  Bulk	Treating. 7.5 Displ. 7.0 Overall 7.5
Sand: Grade None tb. Sack Bulk	PRESSURES-PSI 1st. Stage 3200 Max. 3500
Surfactant: Type None Gal. in Bbl. Gal.	Breakdown 2nd 3100 Maximum 3400
Acid: TypeNoneGol%	Minimum 3000 (3100) Displacement 3400 (330)
Fluid Loss Add.: Type FL-2 /dol. Lb. 1200	Instant Shut-In 1900 (1600) 5 Min 900 (1100)
Perfpac Balls: Type None No.	VOLUMES:
Blocking Agent: Type None Gal. Lb.	Load: Bbl. Gal. Loaded Breakdown: Bbl. 69, 50
Gelling Agent: Type None Gal. Lb.	Treatment: Bbl. Gol. 571 Displ.: Bbl/ Gal. 60
Breaker: Type None Gal. Lb	Total: Bbl/44./ 681

### TREATING LOG

				PRESSU	REPSI	
TIME	Operation or Amt. and Type Fluid Pumped	RATE	PUMPS	TUBING	CASING	REMARKS
	First Stage 4189 - 4212 Feet					
10:45	Pick up pumps & check lines		4	4000	0	
10:55	Breakdown	10.0	3	3100	0	20Bbl. Crude
11:17	Frac @ .5 lb per gal.	6.5	3	3200	0	O Gal.
11:21	Sand on Formation	6.5	3	3150	0	1121 Gal.
11:27 }	l# per gal on Formation	7.0	3	3300	0	2250 Gal.
11:59~	End of sandoil 12,000 Gal.					
	crude & 11.250 lbs. Sand	7.1	3	3400	0	12.500 Gal.
11:59	Flush	7.1	3	3400	0_	O Bbl.
12:03	End flush	7.5	3	3450	0	30 Bbl. crude
	Second stage 4148 - 4165 Feet					
3 - 55		6.0	3	3200_	0_	30 Bbl. Crude
4:00	Frac @ .5# per gal.	6.2	3	3250	0_	0_Gal
4:03	Sand on formation	6.2	<u> </u>	3100	0	1200 Gal.
4:06	3/4# per gal oh formation	7.1	3	3075	0	2400 Gal.
4:08½	1# per gal on formation	8.8	3	<b>9</b> 100	0	3500 Gal.
4:37½	End frac 12,000 gal. crude					
7-712	& 11.250 lbs. 20-40 Sand	7.9	3	3300_	0	12,000 Gal.
÷37₹	Flush	7.9	3	3300		0 Ebl.
4:42	End Flush	6.6	3	3050	ā	30 Bbl. crude
				,,,,		
	One pump not used on either sta	ge be	cause	of p	reasu	re limitations
						ı

Halliburton Operator Kirby - Ferandez

\_Company Representative\_Clayton Johnson

## CORS ANALYSIS ASHLEY VALLEY NO. 1

Poptii	Permahility	Porosity	Water Saturation	Oil Saturation
2030] •	125 md	21.6%	47%	24%
2:31 2	94	19.5	53	29
2032	34	18	61	32
2033}	18	15.7	51	<b>3</b> )
20343	6.3	16.6	68	21
20351	29	17.1	67	09
2036∮	23	16.7	65	21
2037 k	570	21.2	57	26
2038}	600	21.4	60	2.5
27393	40	17	45	15
20403	5	17.5	68	•
2041	ō	7.5	5\$	O
2042	6.8	16.6	62	7
20433	16	17.8	79	12
· · · · · · · · · · · · · · · · · · ·	125	22.1	73	13
20443	100	19.7	82	9
2045}	35	17	69	12
2(146)	3,2	20.4	62	<b>.</b> 8
20479	11.5	15.0	60	11
2048	20	17.1	62	11
2049}	20			

Form DOGC-4

### STATE OF UTAH

## DEPARTMENT OF NATURAL RESOURCES **DIVISION OF OIL & GAS CONSERVATION**

State Lease No	
Federal Lease No.	
Indian Lease No	
Fee & Pat. X	

1588 WEST NORTH TEMPLE SALT LAKE CITY, UTAH 84116 328-5771

# REPORT OF OPERATIONS AND WELL STATUS REPORT

•	STAT	E	U	tah		CC	UNTY_	Unitah	FI	ELD/LEASE	Ashley Valley	
											cing wells) for the month of:	
,	Agent	's Add	dress	Sui	te 806	, #10 W.34	?d 80.		any	EQUITY	DIL COMPANY	
	•••••				L. LAKE.	GLEY, DEA	IA. 841	Signed Title		Constitu		
	Phone	No		B01=	521-35	L5.						
Sec. and % of %		Twp.		Well No.	Days Produced	Barrels of Oil	Gravit	Cu. Ft. of Gas (In thousands)	Gallons of Gasoline Recovered	Water (if	REMARKS (If drilling, depth; if shut down, of date and result of test for gases) content of gas)	use;
Sec. NW S	1	58	22E	1	0	0	0	0	0	0	Well shut in	
Sec. Ne s				2	30	1230	32	4 0	0	244,770		
Sec.	- 1			3	30	675	32	4 0	0	134,325		
Sec.				4	30	630	32.	4 0	0	125,370		
Sec.				51	30	1411	32.	4 0	0	280,589		
Sec.				6	0	0	0	0	0	0	Well shut in	
Sec.2 SE NV				7	30	1456	32.	4 0	0	289,544		
Sec. 2 SE NE				8	0	0	0	0	0	0	Well shut in	
Sec.2 SW NW	13			8	0	•	0	0	0	0	Well shut in	
Sec.2 NW SW	~			10	0	5402	0	0	0	0	Well shut in	
									e e			
	S: (M				<b>V</b>	<b></b>		OIL or CO	NDENSAT	E: (To be reco	orted in Barrels) 1310.66	
S	old	\\en+^			None			On han	d at beginni	ing of month	1310.66 5406.02	
U	sed O	n/Off	Lease _	********			*********	Produce Sold de	ed during m Iring month	onth	5406.02 5952.51	
								Unavoid	dably lost		0	
								<b>O</b> t	Reason:		764,17	
					•			On hand	at end of	month	/04.1/	

Form DCGC-4

### STATE OF UTAH

## DEPART **DIVISION**

STATE OF UTAH	State Lease No.
MENT OF NATURAL RESOURCES	Federal Lease No
OF OIL & GAS CONSERVATION	Indian Lease No.
	Indian Lease No.

1588 WEST NORTH TEMPLE SALT LAKE CITY, UTAH 84116 328-5771

# REPORT OF OPERATIONS AND WELL STATUS REPORT

•	STAT	E	U	tah	***********	co	UNTY	Uintah	Fi	IELD/LEASE	Ashley Valley
-	The f	follow	ing is	a cor	rect repor		ns and r	production (incl			ucing wells) for the month of:
	Agent	's Ad	dress	Sui:	e 806, Lake C	#10 W. 3: ity, Utah	rd Sou 84101	Signed		~ ~ ()	Company
F	hone	No.		801-	·521 <b>-3</b> 5	15		Title		Enginee	
Jac Pn <b>d</b> 4 of 4		Twp	Range	Well No.	Days Produced	Barrets of Oil	Gravity	Cu. Ft. of Gas (!n thousands)	Gallons o Gasoline Recovered		REMARKS (If drilling, depth; if shut down cause date and result of test for gasetin content of gas)
Sec NW		48	22#E	1	0	0	0	0	0	•	Well shut in.
Sec. 2	1			2	31	1276	32.4	0	0	252,924	
Sec. 2: NW SE	3			3	31	700	•	0	0	138,800	
Sec. 23 HW SE	3		Processing a	4	31	653	•	0	0	129,547	
Sec.22 NE SE	2	į		5	31	1462	•	0	0	289,938	·
Sec.22 SE NE	3			65	0	o	o	0	0 -	0	Well shut in.
50c.23 Se nw				7	31	1510	32.	• 0	0	299,290	
Sec.23 SE NE			1	8	0	0	0	o	0	0	Well shut in
iec.23 In na				9	0	o	0	o	0	0	Well shut in
iec.23 IN SW				10	0	o	0	o	0	0	Well shut in
						5601			i	1,110,499	
		:			:						

GAS: (MCF) SoldNone NA	OIL or CONDENSATE: (To be rep On hand at beginning of month_ Produced during month	orted in Barrels) 764.17
Flared/Vented	Produced during month  Sold during month	5600.86
Used On/Off Lease	Sold during month	4967.07
	Unavoidably lost	0
	Reason:	0
	On hand at end of month	1397.96

DRILLING/PRODUCING WELLS: This report must be filed on or before the sixteenth day of the succeeding month following production for each well. Where a well is temporarily shut-in, a negative report must be filed. THIS REPORT MUST BE FILED IN DUPLICATE.

15396 Ashley Valley Jee#1 300 23, T5SO, R22E Bubly 4/26/89 O well head

# STATE OF UTAH DIVISION OF OIL, GAS AND MINING

	S. LEASE DESIGNATION & SERIAL NO.
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL M GAS	7. UNIT AGREEMENT NAME
WELL A WELL OTHER	8. FARM OR LEASE NAME
Equity Oil Company	Meagher
P O Box 959, Salt Lake City Ut 84110-0959	9. WELL NO. #1
OCATION OF WELL (Report location cleany and in accordance with any State requirements.	- Ashley Valley - Wel
** Surface 2665' FNL & 725' FWL, Sec 23-5S-22E	11. SEC., T., R., M., OR BLK, AND
AL proposed prod. zone	NW4SW4, Sec. 23, T5S,
4304715396   15. ELEVATIONS (Show wastner DF, RT, GR, etc.)	Uintah Utah
Check Appropriate Box To Indicate Nature of Notice, Report or	
NOTICE OF INTENTION TO:	SEQUENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT  MULTIPLE COMPLETE  FRACTURE TREATMENT  SHOOTING OR ACIDIZING  SHOOTING OR ACIDIZING	ALTERING CASING ABANDONMENT
SHOOT OR ACIDIZE ABANDON SHOOTING OR ACIDIZING	·——· 17 C + - +   —— 1
* constant	c nerr coacae   XI
REPAIR WELL CHANGE PLANS (Other) P TESENT	its of multiple completion on Well
REPAIR WELL CHANGE PLANS (Other) P TESENT	
APPROX. DATE WORK WILL START CHANGE PLANS * (Other)	ve pertinent dates, including estimated date of
APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give starting any proposed work. If well is directionally drilled, give subsurface locations and measured and pertinent to this work.)	ve pertinent dates, including estimated date of
CHANGE PLANS  (Other)  ** (Other)  (Note: Report results ANNUAL START  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give starting any proposed work. If well is directionally drilled, give state and pertinent to this work.)  ** Must be accompleted to the start of the start o	ve pertinent dates, including estimated date of
REPAIR WELL  (Other)  CHANGE PLANS  * (Other)  * (Other)  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give starting any proposed work. If well is directionally drilled, give subsurface locations and measured and pertinent to this work.)  * Must be accompany.	ve pertinent dates, including estimated date of
CHANGE PLANS  (Other)  ** (Other)  (Note: Report results ANNUAL START  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give starting any proposed work. If well is directionally drilled, give state and pertinent to this work.)  ** Must be accompleted to the start of the start o	ve pertinent dates, including estimated date of
CHANGE PLANS  (Other)  ** (Other)  (Note: Report results ANNUAL START  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give starting any proposed work. If well is directionally drilled, give state and pertinent to this work.)  ** Must be accompleted to the start of the start o	ve pertinent dates, including estimated date of
CHANGE PLANS  (Other)  ** (Other)  (Note: Report results ANNUAL START  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give starting any proposed work. If well is directionally drilled, give state and pertinent to this work.)  ** Must be accompleted to the start of the start o	ve pertinent dates, including estimated date of
CHANGE PLANS  (Other)  ** (Other)  (Note: Report results ANNUAL START  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give starting any proposed work, if well is directionally drilled, give state and pertinent to this work.)  ** Must be accompleted to the starting and the starting and the starting and the starting and pertinent to this work.)	ve pertinent dates, including estimated date of a true versical depths for all markers and zones companied by a cement verification report.
CHANGE PLANS  (Other)  ** (Other)  (Note: Report results ANNUAL START  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give starting any proposed work, if well is directionally drilled, give state and pertinent to this work.)  ** Must be accompleted to the starting and the starting and the starting and the starting and pertinent to this work.)	JAN 2 4 1592  DIVISION OF
REPAIR WELL  (Other)  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giv starting any proposed work. If well is directionally drilled, give subsurface locations and measured and pertinent to this work.)  * Must be acco  Well currently shut in.  Uneconomic under present market conditions.	JAN 2 4 1592  DIVISION OF
REPAIR WELL  (Other)  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and go starting any proposed work. If well is directionally drilled, give subsurface locations and measured and pertinent to this work.)  * Must be acco  Well currently shut in.  Uneconomic under present market conditions.	JAN 2 4 1992  DIVISION OF OIL GAS & MINING
REPAIR WELL  (Other)  APPROX. DATE WORK WILL START  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and giv starting any proposed work. If well is directionally drilled, give subsurface locations and measured and pertinent to this work.)  * Must be acco  Well currently shut in.  Uneconomic under present market conditions.	JAN 2 4 1992  DIVISION OF OIL GAS & MINING

STATE OF UTAH		•	
DIVISION OF OIL, GAS AND MINIM	NG		•
·	`	S. LEASE DESIGNATION	E SERIAL NO.
		6. IF INDIAN. ALLOTTEE	OR TRIBE MAME
SUNDRY NOTICES AND REPORTS ON (Do not use this form for proposals to drill or to deepen or plug back use "APPLICATION FOR PERMIT—" for such proposals to the pr	to a different teservou.		
		T. UNIT AGREEMENT NA	ZIE /
WELL X WELL OTHER		IS. FARM OR LEASE HAM	· ·
Equity Oil Company		Meagher	<u> </u>
P O Box 959, Salt Lake City Ut 8	4110-0959	9. WELL NO. #1	
LOCATION OF WELL (Report location cleany and in accordance with any State require	ments	- Ashley Va	11ey - Weber
At surface 2665' FNL & 725' FWL, Sec 23-5S-	22E	NW4SW4, Sec.	23, T5S, R22
4304715396 IS ELEVATIONS (Show whether DF. R	RT. GR. «LC.)	Uintah	Utah
c. Check Appropriate Box To Indicate Nat	ture of Natice, Report or O	Ither Data	
NOTICE OF INTENTION TO:	SZEUZ	OUENT REPORT OF:	
TEST WATER SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING	
FRACTURE TREAT MULTIPLE COMPLETE	FRACTURE TREATMENT SHOOTING OR ACIDIZING	ALTERING O	<del></del>
SHOOT OR ACIDIZE ABANDON  BERAIR WELL	* Present	Well Status	$\overline{\mathbf{x}}$
REPAIR WELL CHANGE PLANS (Other)	(Note: Report result *ANNUAL STATU	Sunfered Sebdir and Pos	form.)
APPROX. DATE WORK WILL START	DATE OF COMPLETION .		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly starting any proposed work. If well is directionally drilled, give subsurface pertinent to this work.)	is locations and memories and		
parameter man record	* Must be accor	mpanied by a cement ve	rification report.
Well currently shut in.			
Uneconomic under present market	t conditions.		



DIVISION OF CIL GAS & MINING

SIGNED	TITLE Petroleum Engineer	DATE
(This space to Foderal or State office use)		
APPROVED BY	1111E	DATE

January 4, 1993

Re: Annual Status Report Shut-in Wells Ashley Valley Field Uintah Co., Carbon Co., Utah

State of Utah Department of Natural Resources Division of Oil, Gas and Mining 355 West North Temple 3 Triad Center, Suite 350 Salt Lake City, Ut 84180-1203

### Gentlemen:

ţ

Please find enclosed the Annual Status Report of the above referenced fields as per your recent communication of December 4, 1992.

If additional information is required, please advise.

Sincerely,

EOUITY OIL COMPANY

Vim Larson

Petroleum Engineer

JL:jf

enclosures

DIVISION OF OIL GAS & MINING

# STATE OF UTAH DIVISION OF OIL. GAS AND MINING

-EB 2 1996

	S. LEASE DESIGNATION & SERIAL NO.	
	Fee	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.	6. IF INDIAN, ALLOTTEE OR TRIBE MAME	
Use "APPLICATION FOR PERMIT—" for such proposals.)	T. UNIT AGREEMENT NAME	
OIL A GAS WELL OTHER	I 8. FARM OR LEASE NAME	
Equity Oil Company	Meagher  ** WELL NO.  #1	
P O Box 959, Salt Lake City Ut 84110-0959		
OCATION OF WELL (Report location cleany and in accordance with any State requirements.	IG. FIELD AND POOL, OR WILDCAT	
ree also space 17 below.) NW4SW4  N. Surface 2665' FNL & 725' FWL, Sec 23-5S-22E  Al proposed prod. zone	- Ashley Valley - Webe	
4304715396 IS. ELEVATIONS (Show whether DF, RT, GR, etc.)	Uintah Utah	
Check Appropriate Box To Indicate Nature of Notice, Report or	Other Data	
•••	SEQUENT REPORT OF:	
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	<del>  </del>	
REPAIR WELL CHANGE PLANS (Note: Report res	t Well Status X  ults of multiple completion on Well eggmulatip deptr and Log form.)	
APPROX. DATE WORK WILL START DATE OF COMPLETION		
DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and generally drilled, give subsurface locations and measured an pertinent to this work.)  * Must be acc	ive pertinent dates, including estimated date of direction depths for all markers and zones companied by a cement verification report.	
Well currently shut in.		
Uneconomic under present market conditions.	•	
I have by costiff that the (greenity is true and correct		
. I hereby certify that the foregoing is true and correct  SIGNED TITLE Petroleum Engine	er DATE 01/31/96	

# STATE OF UTAH DIVISION OF OIL, GAS AND MINING

			5. Lease Designation and Serial Number: Fee
SUNDRY NOTICES AND REPORTS ON WELLS			6. If Indian, Allottee or Tribe Name:
Do not use this form for proposals to drill new wells, deepen existing wells, or to reenter plugged and abandoned wells.			7. Unit Agreement Name:
Use APPLICATION FOR PERMIT TO DRILL OR DEEPEN form for such proposals.  1. Type of Well:  OIL   GAS   OTHER:			8. Well Name and Number: Meagher #1
2. Name of Operator: Equity Oil Company			9. API Well Number: 4304715396
3. Address and Telephone Number: P.O. Box 959 Salt Lake City, UT. 84101 (801) 521-3515			10. Field and Pool, or Wildcat: Ashley Valley-Weber
4. Location of Well Footages: 2665' FNL, 725' FV QQ, Sec., T.,R.,M.: NW SW Sec 23, 5	SS, 22E	NATURE OF NOTICE, REPO	county: Uintah State: UT  DRT, OR OTHER DATA
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT NOTICE OF INTENT SUBSEQUENT REPORT NOTICE OF INTENT			
(Submit in Dup	licate)	(Submit Original Form O	only)
☐ Abandonment	☐ New Construction	☐ Abandonment*	☐ New Construction
Casing Repair	☐ Pull or Alter Casing	☐ Casing Repair	☐ Pull or Alter Casing
☐ Change of Plans	☐ Recompletion	☐ Change of Plans	☐ Shoot or Acidize
☐ Conversion to Injection	☐ Shoot or Acidize	☐ Conversion to Injection	☐ Vent or Flare
☐ Fracture Treat	☐ Vent or Flare	☐ Fracture Treat	☐ Water Shut-Off
☐ Multiple Completion	☐ Water Shut-Off	Other <u>Present Well Sta</u>	tus - Annual Status Report
Other		Date of work completion	
Approximate date work will start Report results of Multiple Con		1	Recompletions to different reservoirs on WELL
		* Must be accompanied by a cement verificatio	
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (C markers and zones pertinent to this work.)	learly state all pertinent details, and give	pertinent dates. If well is directionally drilled, give subs	surface locations and measured and true vertical depths for all
Well currently shut in.			
Uneconomic under present m	arket conditions.	<del></del>	
		DIV	FEB 0 3 1997 COF OIL, GAS & MINING
Name & Signature: Brew P. Ma  (This space for State use only)	rchant	Title: Staff Operations Engine	er Date:01/31/97


(See Instructions on Reverse Side)

### STATE OF UTAH

	DEPARTMENT OF NATURAL DIVISION OF OIL, GAS		•				
	2.7101011 01 OIL, GAO 7		5. Lease Designation and Serial Number:				
			Fee				
SUNDRY NOTICE A	ND REPORTS ON WEL	LS	6. If Indian, Allottee or Tribe Name:				
Do not use this form for proposals to drill new wells, deepen existing wells, or to reenter plugged and abandoned wells.  Use APPLICATION FOR PERMIT TO DRILL OR DEEPEN form for such proposals.		NA 7. Unit Agreement Name: NA					
				1. Type of Well:		8. Well Name and Number:	
				■ OIL □ GAS OTHER: SI		Ashley Valley - Meagher #1	
2. Name of Operator:	<b>3.1.3</b>		9. API Well Number:				
Equity Oil Company			43-047-15396				
3. Address and Telephone Number:	(801) 521-3515		10. Field and Pool, or Wildcat:				
10 West Third South, Suite 806 / P.O.	Roy 050 Salt Lake City LIT	94110 0050	i '				
4. Location of Well	DOX 909 Gait Lake City, OT	04110-0939	Ashley Field - Weber				
Footages: 2665' FN	IL. 725' FWL	Cor	unty: <i>Uintah</i>				
_			•				
QQ,Sec.,T.,R.,M.; NESW S			state: Utah				
	KES TO INDICATE NATURE OF I						
NOTICE OF INTENT (submit in dupticate)	Γ		UENT REPORT				
☐ Abandonment	□ New Construction	☐ Abandonment	New Construction				
Casing Repair	☐ Pull or Alter Casing	Casing Repair	☐ Pull or Alter Casing				
Change of Plans	☐ Recompletion	☐ Change of Plans	□ Recompletion				
Conversion to Injection	☐ Shoot or Acidize	Conversion to In	ejection				
☐ Fracture Treat	☐ Vent or Flare	Fracture Treat	☐ Vent or Flare				
Multiple Completion	☐ Water Shut-Off	Multiple Complet					
Other: Shut-In Status		■ Other: <u>Shut-In</u>	Status				
Approximate date work will start:		Date of work com	pletion:				
		Report results of Multipl	le Completion and Recompletions to different reservoirs on				
			R RECOMPLETION AND LOG form. ad by a cement verification report.				
		must be acompani	eo by a cement verification report.				
2. DESCRIBE PROPOSED OR COMPLETED OPER	RATIONS (Clearly state all pertinent deta	ails, and give pertinent dates. If well	is directionally drilled, give subsurface locations and				
measured and true vertical depths for all marke			•				
Ashley Valley (Meagher Fee) #1 is	SI because it's high water	er/oil ratio (WOR) make	s the well uneconomic to produce at current oil prices.				
The subject well is SI at the surfac	e with no visible leaks. Si	ince the Ashley field We	eber Fm. wells are capable of flowing several hundred				
barrels of fluid per day, the absenc	e of flow demonstrates m	nechanical integrity at th	he surface.				
Equity Oil Company requests that t	the SI status of Ashley Va	alley #1 be extended fo	r a period of one year.				
Soo analoged latter for furth i-f-	ation						
See enclosed letter for further infor	mauon.						
APPROVE	.D		गरमाञ्चा ची ता				

The Utah Division of Oil, Gas and Mining Robert J. Krueger, PE, Petroleum Engineer


Date: 3.17-99



		48
13.	<u> </u>	
Name & Signature: <u>Brent P. Marchant</u>	Brent P. Marchant	Title: <u>Production Manager</u> Date: <u>03/16/99</u>
(This space for State use only)		

Mr. John Baza
State of Utah
Department of Natural Resources
Division of Oil, Gas and Mining
P.O. Box 145801
Salt Lake City, UT 84114-5801

Re: Ashley Valley Shut-In (SI) Wells



March 16, 1999

As per your correspondence dated February 17, EQUITY OIL COMPANY (EOC) operates four SI wells (#1, #3, #6 and #8) in the Ashley Valley field.

EOC has been evaluating modern water shut off (WSO) techniques to determine if some type of WSO could eventually make restoring production from the SI wells economic. In 1996, all of the EOC SI wells were evaluated for future productive potential. At that time wells #9 and #10 were deemed to be the two least likely WSO candidates. The two wells were then plugged and abandoned.

A MARCIT<sup>SM</sup> WSO treatment was performed on Ashley Valley #2 in 1997. Although technically successful, the treatment did not prove to be economic at the current oil price. We believe an oil sales price of \$20/BO (minimum) at Ashley Valley is needed to justify the WSO treatments on SI wells. When economically feasible, a significant oil reserve is present in the SI wells. When these wells are plugged, the potential oil reserves will be lost.

Please see enclosed, four Sundry Notices requesting extension of SI status for Ashley Valley wells #1, #3, #6 and #8.

Thank you for your consideration of this matter.

Sincerely,

Brent P. Marchant

Brent P. Marchant Production Manager

**Enc: Four Sundry Notices** 

cc: Dave Seery

C:\MyFiles\BPM\990316.wpd



Department of Natural Resources

Division of Oil, Gas & Mining

ROBERT L. MORGAN Executive Director

LOWELL P. BRAXTON Division Director MICHAEL O. LEAVITT Governor

OLENE S. WALKER Lieutenant Governor

April 16, 2004

CERTIFIED MAIL NO. 7002 0510 0003 8602 6303

Carlos Rivera Equity Oil Company P.O. Box 310 Cody, Wyoming 82414

Re: Extended Shut-in and Temporary Abandoned Well Requirements for Fee or State Leases.

Dear Mr. Rivera:

Equity Oil Company, as of April 2004, has two (2) Fee Lease Wells (see attachment A) that are currently in non-compliance for extended shut-in or temporary abandonment status. Wells SI/TA beyond twelve (12) consecutive months requires filing a Sundry Notice (R649-3-36-1). Wells with five (5) years non-activity or non-productivity shall be plugged, unless the Division grants approval for extended shut-in time upon a showing of good cause by the operator (649-3-36-1.3.3). For extended SI/TA consideration the operator shall provide the Utah Division of Oil, Gas & Mining with the following:

- 1. Reasons for SI/TA of the well (R649-3-36-1.1).
- 2. The length of time the well is expected to be SI/TA (R649-3-36-1.2), and
- 3. An explanation and supporting data if necessary, for showing the well has integrity, meaning that the casing, cement, equipment condition, static fluid level, pressure, existence or absence of Underground Sources of Drinking Water and other factors do not make the well a risk to public health and safety or the environment (R649-3-36-1.3).



Page 2 April 16, 2004 Carlos Rivera

Submitting the information suggested below may help show well integrity and may help qualify your well for extended SI/TA. Note: As of July 1, 2003, wells in violation of the SI/TA rule R649-3-36 may be subject to full cost bonding (R649-3-1-4.2, 4.3).

- 1. Wellbore diagram, and
- 2. Copy of recent casing pressure test, and
- 3. Current pressures on the wellbore (tubing pressure, casing pressure, and casing/casing annuli pressure) showing wellbore has integrity, and
- 4. Fluid level in the wellbore, and
- 5. An explanation of how the submitted information proves integrity.

If the required information is not received within 30 days of the date of this notice, further actions may be initiated. If you have any questions concerning this matter, please contact me at (801) 538-5281.

Sincerely,

Dustin K. Doucet Petroleum Engineer

jc

cc: Jo

John Baza Well File

# Equity Oil Company

	Well Name	API	Lease Type	Years Inactive
1	Ashley Valley Fee 1	43-047-15396	Fee	11 Years 0 Months
2	Ashley Valley Fed 2-A	43-047-15398	Fee	9 Years 5 Months

Attachment A

# TE OF UTAH DIVISION OF OIL, GAS AND MINING

( <u> </u>	

Dividion of one and the imm		5. Lease Designation and Serial Number: Fee
SUNDRY NOTICES AND REPORTS	ON WELLS	6. If Indian, Allottee or Tribe Name;
Do not use this form for proposals to drill new wells, deepen existing wells, or to reente Use APPLICATION FOR PERMIT TO DRILL OR DEEPEN form for su	or plugged and abandoned wells.	7. Unit Agreement Name:
1. Type of Well: OIL X GAS OTHER: SI	·	8. Well Name and Number:
2 Name of Operator: Equity Oil Company	43	9. API Well Number: -047-15396
3. Address and Telephone Number: PO Box 310 Cody, WY 82414	(307) 587–7812	10. Field and Pool, or Wildcat: Ashley Valley-Weber
4. Location of Well 2665 'FNL, 725 'FWL		County: Uintah
QQ, Sec.,T.,R.,M.: NW SW 23, 5S, 22E		State: UT
11. CHECK APPROPRIATE BOXES TO INDICATE N	ATURE OF NOTICE, REPOF	IT, OR OTHER DATA
NOTICE OF INTENT (Submit in Duplicate)		JENT REPORT riginal Form Only)
	☐ Abandonment *	☐ New Construction
☐ Casing Repair ☐ Pull or Alter Casing	Casing Repair	Pull or Alter Casing
☐ Change of Plans ☐ Recompletion	☐ Change of Plans	☐ Shoot or Acidize
☐ Conversion to Injection ☐ Shoot or Acidize	☐ Conversion to Injection	☐ Vent or Flare
☐ Fracture Treat ☐ Vent or Flare	☐ Fracture Treat	
☐ Multiple Completion ☐ Water Shut-Off	Other	
Other		
•	Date of work completion	
Approximate date work will start	Report results of Multiple Completions and	d Recompletions to different reservoirs on WELL
	COMPLETION OR RECOMPLETION AND L	
• •	Must be accompanied by a cement verifica	tion report.
Equity Oil Company plans to plug and abando	on Ashley #1 as shown o	on attached sheet.
	R	ECEIVED
COPY SENT TO OPEN SENT	M	1AY 0 4 2004
Side: 5-19.04 Initials: CHO	DIV. O	FOIL, GAS & MINING
A Secretaria de la constante d		
13. Name & Signature: Brent P. Marchant	Title: Production M	lanager 04/28/04
This space for State use only)  APPROVED BY THE STATE  OF UTAH DIVISION OF  OIL, GAS, AND MINING  DATE SHOW  BY:  See Conditions of Approva  ** See Conditions of Approva  ** See Letter dated May 1012	-	
A DEC POTIES CONTO		

(1\93)

April 28, 2004

Equity Oil Company, Ashley Fee #1 Sundry Attachment

### Notice of Intent - Plug and Abandon

- 1. Dig earthen pit adjacent to wellhead. Flow well to pit while removing upper wellhead (well flows 99.5% fresh water).
- 2. Install 6", 3M double gate BOP with 2 7/8" pipe rams in top gate and blind rams in bottom gate. Function test BOP.
- 3. P&SB 2 7/8" tubing.
- 4. RU wireline equipment. Run CICR for 7", 20/23# casing and set at about 3990'-above 5" liner top.
- 5. Squeeze Weber perfs (4148' 4212', gross interval in 5" liner) with 70 sks premium cement. Plan to pump 60 sks below CICR and leave 10 sks on top.
- 6. Circulate hole with about 155 bbls corrosion inhibited fresh water.
- 7. Set 30 sk balanced premium cement plug across top of Chinle Fm. about 3000' 3150'.
- 8. Perforate squeeze holes at 556'. Set CICR at about 500'.
- 9. Squeeze base of 10 ¾" surface casing with 45 sks premium cement to a max pressure of 200 psi. If the cement circulates to surface on the 7" x 10 ¾" annulus, 60 sks will be pumped.
- 10. Remove BOPE and cut off tubing and casing heads. Set 10 sk surface plug in 7" casing. Place 20 sks cement in 7" x 10 3/4" annulus (about 60') as needed, and 20 sks cement in 10 3/4" x 16" annulus (about 30') thru 1" pipe.
- 11. Weld DHM cap on 10 3/4' casing and bury about 3' BGL.

Ashley1SA042804.doc



State of Utah

Department of Natural Resources

ROBERT L. MORGAN Executive Director

Division of Oil, Gas & Mining

LOWELL P. BRAXTON
Division Director

OLENE S. WALKER Governor

GAYLE F. McKEACHNIE
Lieutenant Governor

## CONDITIONS OF APPROVAL TO PLUG AND ABANDON WELL

Well Name and Number:

Ashley Valley Fee #1

API Number:

43-047-15396

Operator:

**Equity Oil Company** 

Reference Document:

Original Sundry Notice Dated April 28, 2004

Received by DOGM on May 4, 2004

### **Approval Conditions:**

- 1. Notify the Division at least 24 hours prior to conducting abandonment operations. Please call Dan Jarvis at 801-538-5338.
- 2. Balanced plugs shall be tagged to ensure the plugs are at the depths specified in the proposal.
- 3. ADD PLUG from +/- 1,100' to 1,000' with CICR @ +/- 1,050', squeeze holes @ 1,100', pump 45 sacks through CICR and spot 10 sacks on top. Isolate Cretaceous Formations from the Jurassic Formations.
- 4. Surface reclamation shall be done in accordance with R649-3-34 Well Site Restoration. Evidence of compliance with this rule should be supplied to the Division upon completion of reclamation.
- 5. All requirements in the Oil and Gas Conservation General Rule R649-3-24 shall apply.
- 6. If there are any changes to the plugging procedure or the wellbore configuration, notify Dustin Doucet at 801-538-5281 prior to continuing with the procedure.

7. All other requirements for notice and reporting in the Oil and Gas Conservation General Rules shall apply.

Dustin K. Doucet Petroleum Engineer May 10, 2004

Date

Utah!
Where ideas connect\*\*

Wel	lbore Dia	gram	Page 1			r263
API Well No: 43-047-15396-00-00 Permit No:	*****	Well Nam	e/No: ASHI	LEY VALLI	EY FEE 1	
Company Name: EQUITY OIL COMPANY						
Location: Sec: 23 T: 5S R: 22E Spot: NWSW	String Info	ormation				
<b>Coordinates:</b> X: 634253 Y: 4469721	_	Bottom	Diameter	Weight	Length	
Field Name: ASHLEY VALLEY	String	(ft sub)	(inches)	(lb/ft)	(ft)	
County Name: UINTAH	HOL1	506	13.25			
	SURF	506	10.75	32.7	1,8	7
Juf Senf-(0)(1.18)(4.524)=50f Annul 7-16.25 = (0)(1.18)(3.341)=78	HOL2	4134	9		4.524 -	-3.341
Annul 7-16.75 = (20)(1.18)(3.341)= 78	PROD	4134	7	23	4.534	1
Cement from 506 ft. to surface	HOL3 L1	4285	6.25 5	15		
Hole: 13.25 in. @ 506 ft.		4285	3	13		
Topide (0) (1.18)(4.5341) = 13  Bookside 50/1.18)(2.71) = 15	dear	j <sup>-</sup>	`	12 _2		
Surface: 10.75 in. @ 506 ft. Dro Red her Cast ve	,	[(	(1.2)(9)	- 75	2.71	
506 SG2 hules			(1.2)(9) (43.	>	- C # //	
Trails 100/(1118)(4.524) = 1	9		142.	2)		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	•					
1 1 2 march (1) 2 - 21) = 15	•					
Bookside Soffice Con una	Es Cement In	formation				
1	Stulma.	BOC	TOC	Class	C. I.	
			, , , ,	Class	Sacks	
lugo at.	PROD	4285 4134		A UK	30 300	
Cicher sor boles 1100	SURF	506		UK	235	
P1 above 50/((.18)(4,524)=1	251c5	300	v	O.K	233	
below 100/(1.16)(2.71) = 32.5ks						
be(w) 800/						
Delow 100 /(1/18) (2.71) - 5000						
	Perforation	n Informati	ion			
	Тор	Bottom				
	(ft sub)	(ft sub)	Shts/l	Ft No Sh	ts Dt Squeeze	
	4148	4212				
Balance Plug 3000-3150  Teoleten  Gran  100/(1.18)(4.524) = 20 5 k3	riske su	ion				
Tesliter	in crisic .					
Polance bing the	100					
100/(1/18)(4.524) = 20 5K3						
3-TOC 3178	Formation	Informatio	n			
Programme (Control of the Control of	Formatio	-	Fo	rmation	Depth	
d of the second	FRTR DKTA	690 1020				
	MORN	1073	<del>-</del>			
Hole: 9 in. @ 4134 ft.	CRTS	1970				
Time from 4205 A to 4020 C to pub.	ENRD	2046				
Liner from 4285 ft. to 4038 ft.	CARM	2280				
Production: 7 in. @ 4134 ft. 1	NAVA	2408				
plag 1 (0)(118)4.524	SRMP	3120 3200				
Hole: 9 in. @ 4134 ft.  Liner from 4285 ft. to 4038 ft.  Production: 7 in. @ 4134 ft.  CICLE 39 90  Plug 1  Hole: 6.25 in. @ 4285 ft.  Selow (222 (118) (4:534) = 4)	SKM MNKP	3306				
below &	PSPR	3990				
<b>TD:</b> 4152 <b>TVD: PBTD:</b>	£	± 3800	) <sup>(</sup>			
Copyright 2001 ALL-LLC	シャいしい	1 / 10-0			******	



Department of Natural Resources

Division of Oil, Gas & Mining

ROBERT L. MORGAN Executive Director

LOWELL P. BRAXTON
Division Director

May 10, 2004

CERTIFIED MAIL NO. 7002 0510 0003 8602 5429

Mr. Brent Marchant Equity Oil Company P.O. Box 310 Cody, Wyoming 82414

Re: Extended Shut-in and Temporary Abandoned Well Requirements for Fee or State Leases dated April 16, 2004.

Dear Mr. Marchant,

The Division of Oil, Gas and Mining (DOGM) is in receipt of your sundries dated April 28, 2004 (received by the division on 5/04/2004) in regards to the two (2) shut-in wells operated by Equity Oil Company (Equity).

It is the Division's understanding Equity intends to plug the Ashley Fee #1 this year. The DOGM approves extended SI/TA for the Ashley Fee #1 until January 1, 2005, providing Equity with sufficient time to plug the well.

Due to the lack of sufficient evidence the DOGM is unable to grant extended SI/TA status for the Ashley Valley Federal #2A. As requested in our April 16, 2004 correspondence, the DOGM requires the anticipated length of time the well is expected to remain shut-in (R649-3-36-1.2) and an explanation of how the submitted information proves integrity was not submitted. Also, for continued shut-in status a plan of how the well fluid and pressures will be monitored and reported in the future should be provided. Please submit the required information for the Ashley Valley Federal #2A in the next 30 days or further action may be initiated.

For reference, Attachment A lists the wells subject to this request. If you have any questions or need additional assistance in regards to the above matters please contact me at (801) 538-5281.

Dustin Doucet Petroleum Engineer



C.C. Well File

Well Name	API	Lease Type	Years Inactive
1 Ashley Valley Fee 1	43-047-15396	Fee	11 Years 0 Months
2 Ashley Valley Fed 2-A	43-047-15398	Fee	9 Years 5 Months

### **OPERATOR CHANGE WORKSHEET**

ROUTING
1. GLH
2. CDW
3. FILE

## X Change of Operator (Well Sold)

The operator of the well(s) listed below has changed, effective:

Designation of Agent/Operator

9/1/2004

Operator Name Change

Merger

FROM: (Old Operator):				TO: ( New Operator):					
N0410-Equity Oil Company				N2680-Whitin	- '	Corporation	1		
PO Box 310				1700 F	- Broadway, S	uite 2300			
Cody, WY 84414-0310				Denve	r, CO 80290	)			
Phone: 1-(307) 587-7812				Phone: 1-(303)	837-1661				
CA No.	•			Unit:					
WELL(S)			·						
NAME	SEC	TWN	RNG	API NO	ENTITY	LEASE	WELL	WELL	
					NO	TYPE	TYPE	STATUS	
ASHLEY VALLEY 5	22	050S		4304715401	260	Fee	ow	P	
ASHLEY VALLEY FEE 1	23			4304715396	260		OW	S	
ASHLEY VALLEY 2	23			4304715397	260	Fee	OW	P	
ASHLEY VALLEY FED 2-A	23	050S		4304715398	10682	Fee	GW	S	
ASHLEY VALLEY 4	23	050S		4304715400	260	Fee	OW	P	
ASHLEY VALLEY 7	23	050S	220E	4304715403	260	Fee	OW	P	
ASHLEY VALLEY FEE 11-5	23	050S	220E	4304715407	99998	Fee	NA	PA	
ASHLEY VALLEY 1-E	23	050S	220E	4304720251	99998	Fee	NA	PA	
PREECE 1	19	050S	230E	4304710363	99998	Fee	OW	PA	
	<u></u>	<u> </u>							
					L	,			
		1							
	1	1							
OPERATOR CHANGES DOCUMENT Enter date after each listed item is completed 1. (R649-8-10) Sundry or legal documentation w 2. (R649-8-10) Sundry or legal documentation w	as rec	ceived f	rom the	NEW operator	on:	9/1/2004 9/1/2004		0/00/0004	
3. The new company was checked on the <b>Depart</b>		of Cor			_			9/28/2004	
4. Is the new operator registered in the State of U	Jtah:		YES	Business Numl	ber: 5	426359-014	3		
5. If NO, the operator was contacted contacted o	n:							ν	
6a. (R649-9-2)Waste Management Plan has been r	eceive	ed on:		IN PLACE					
6b. Inspections of LA PA state/fee well sites comp				***	- All transfe	rred to Wh	itina Oil a	as thev	
or mappedione of Mark 11 button 100 went blood comp						Equity Oil's	_	<b></b>	

<ol> <li>Federal and Indian Lease Wells: The BLM and or the or operator change for all wells listed on Federal or Indian leases</li> </ol>		the merger, name change,  LM n/a BIA n/a
8. Federal and Indian Units: The BLM or BIA has approved the successor of unit operator:	for wells listed on:	n/a
<ol> <li>Federal and Indian Communization Agreements ( The BLM or BIA has approved the operator for all wells listed</li> </ol>	l within a CA on:	n/a
10. Underground Injection Control ("UIC") The Inject, for the enhanced/secondary recovery unit/project for the		UIC Form 5, Transfer of Authority to isted on:
DATA ENTRY:		
1. Changes entered in the Oil and Gas Database on:	9/30/2004	
2. Changes have been entered on the Monthly Operator Change	Spread Sheet on:	9/30/2004
3. Bond information entered in RBDMS on:	9/30/2004	
4. Fee/State wells attached to bond in RBDMS on:	9/30/2004	
5. Injection Projects to new operator in RBDMS on:	n/a	
6. Receipt of Acceptance of Drilling Procedures for APD/New on:		n/a
FEDERAL WELL(S) BOND VERIFICATION:		
1. Federal well(s) covered by Bond Number:	n/a	
INDIAN WELL(S) BOND VERIFICATION:		
1. Indian well(s) covered by Bond Number:	n/a	
FEE & STATE WELL(S) BOND VERIFICATION: 1. (R649-3-1) The NEW operator of any fee well(s) listed covered	d by Bond Number	RLB0004585
2. The <b>FORMER</b> operator has requested a release of liability from The Division sent response by letter on:	their bond on: n/a	*** Whiting assumed Equity's bond
LEASE INTEREST OWNER NOTIFICATION: 3. (R649-2-10) The FORMER operator of the fee wells has been of their responsibility to notify all interest owners of this change	contacted and informed on: 10	by a letter from the Division /5/2004
COMMENTS:		

# STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OU. GAS AND MINING

	DIVISION OF OIL, GAS AND MI	NING	5. LEASE DESIGNATION AND SERIAL NUMBER: See attached list
SUNDRY	NOTICES AND REPORTS	S ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: N/A
Oo not use this form for proposals to drill new drill horizontal late	w wells, significantly deepen existing wells below our erals. Use APPLICATION FOR PERMIT TO DRILL f	rrent bottom-hole depth, reenter plugged wells, or to form for such proposals.	7. UNIT OF CA AGREEMENT NAME:
1. TYPE OF WELL OIL WELL [	GAS WELL OTHER_		8. WELL NAME and NUMBER: See attached list
2. NAME OF OPERATOR: Whiting Oil and Gas Corpor	ration		9. API NUMBER:
3. ADDRESS OF OPERATOR:  1700 Broadway #3300		80290 PHONE NUMBER: (303) 837-1661	10. FIELD AND POOL, OR WILDCAT:
4. LOCATION OF WELL FOOTAGES AT SURFACE:			None of the second
QTR/QTR, SECTION, TOWNSHIP, RANGE	E. MERIDIAN:		COUNTY: STATE:
			UTAH
	OPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION	□ ACIDIZE	TYPE OF ACTION	
NOTICE OF INTENT (Submit in Duplicate)  Approximate date work will start:	ACIDIZE  ALTER CASING  CASING REPAIR  CHANGE TO PREVIOUS PLANS	DEEPEN FRACTURE TREAT NEW CONSTRUCTION OPERATOR CHANGE	REPERFORATE CURRENT FORMATION  SIDETRACK TO REPAIR WELL  TEMPORARILY ABANDON  TUBING REPAIR
SUBSEQUENT REPORT (Submit Original Form Only)  Date of work completion:	CHANGE TUBING CHANGE WELL NAME CHANGE WELL STATUS COMMINGLE PRODUCING FORMATIONS CONVERT WELL TYPE	PLUG AND ABANDON PLUG BACK PRODUCTION (START/RESUME) RECLAMATION OF WELL SITE RECOMPLETE - DIFFERENT FORMATION	VENT OR FLARE WATER DISPOSAL WATER SHUT-OFF OTHER:
	inge the Operator of record from	ertinent details including dates, depths, volume in Equity Oil Company to Whiting ( BLM "Bland"#	Oil and Gas Corporation. See
1700 Broadway, Suite 2300 Denver, CO 80290 (303) 837-1661	N 268D	BLM Bond# state/fee Bond#RI	
Equity Oil Company P.O. Box 310 1239 Rumsey Avenue Cody, Wyoming 84414-031	S.	LOVED 9/30/04 lene Rissell	SEP U 1 2004
Equity Oil Company	Bartone l	Russel, Engineering Technicis	DIV. OF OIL, CAS & MINING
HAME (PLEASE PRINT)  GRANTURE  Chitting Oil and Gas Corporation	DAVID M. SEERY	DATE August 2	Egaity Od Conpany Heard Attorney-In-Fact 1, 2004
ME (PLEASE PRINT) James Brown	Sucar	Vice President of Ope	

Pl Well Number	Current Operator	Well Name	Well Type	Wall Status	Location (Twp-Ring								
				7191.00	Location (Twp-Ring	Section	Typpe Tr	Mpd Ring	n Rnad	Qtr/Otr	FL NS	NG D	58/5
3-047-15684-00-00	EQUITY OIL COMPANY	USA PAN AMERICAN 3				1 7					1	- 1.	ENE
-047-15398-00-00	EQUITY OIL COMPANY	ASHLEY VALLEY FED 2-A	Gas Well	Temporarily Shut-In		26	5:S	.   2	22 E	NENW	330	N	1650 W
J-047-15396-00-00	EQUITY OIL COMPANY	ASHLEY VALLEY FEE 1		-	!5S-22E	23	5 5	7	22,E	NWSW	1660		1275 W
-047-15403-00-00	EQUITY OIL COMPANY	ASHLEY VALLEY 7			'5\$-22E	23	5 5	2	2 E	NWSW	2685		725 W
-047-15400-00-00	EQUITY OIL COMPANY	ASHLEY VALLEY 4			5S-22E	23	5 S	2	2 E	SENW	2103		1650 W
-047-15397-00-00	EQUITY OIL COMPANY	ASHLEY VALLEY 2			5S-22E	23	5 S	2	2 E	NWSW	1662		971 W
-047-15686-00-00	EQUITY OIL COMPANY	USA PAN AMERICAN 5			58-22E	23	5 \$	2	2 E	NESW	1686		1680 W
-047-15682-00-00	EQUITY OIL COMPANY	USA PAN AMERICAN 1			5S-22E	26	5 S	2	2 E	NENE	330		980€
-047-15401-00-00	EQUITY OIL COMPANY	ASHLEY VALLEY 5			5S-22E	23	5'\$	2	2 E	SWSW	990		990 W
-047-15685-00-00	EQUITY OIL COMPANY	USA PAN AMERICAN 4			58-22E	22	5 \$	2	2;E	NESE	1890		345 E
-047-10363-00-00	EQUITY OIL COMPANY	PREECE 1		D 0 1	**	22	5 S	_ 2	2 E	SESE	980		330 E
-047-15407-00-00	EQUITY OIL COMPANY	ASHLEY VALEY FEE 11-5		D 0 A	5S-23E	19	5 \$	_ 2	3 E	CNWSW			665 W
-047-20251-00-00	EQUITY O'L COMPANY	ASHLEY VALLEY 1-E		F1 0 4	5S-22E	23	5 S	2	2 E	NWSW	1860		539 W
	<del></del>		100 0400	. 47	5S-22E	23	5 S	2	_	C SW	1335		1320 W

SEP 2 9 2004 (

# RECEIVED JAN 1 3 2005

## STATE OF UTAH PARTMENT OF NATURAL RESOURCES

FORM 9

DEPARTMENT OF NATURA DIVISION OF OIL, GAS	AND MINING DIV. OF OIL, GAS & MINI	NG 5. LEASE DESIGNATION AND SERIAL NUMBER: Fee
SUNDRY NOTICES AND RE	PORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Do not use this form for proposals to drill new wells, significantly deepen existing w drill horizontal laterals. Use APPLICATION FOR PERM	vells below current bottom-hole depth, reenter plugged wells, or to ITTO DRILL form for such proposals.	7. UNIT or CA AGREEMENT NAME:
1. TYPE OF WELL OIL WELL GAS WELL	OTHER	8. WELL NAME and NUMBER:
2. NAME OF OPERATOR:		Ashley Valley Fee #1  9. API NUMBER:
Whiting Oil and Gas Corp		4304715396
3. ADDRESS OF OPERATOR: 1700 Brdwy Ste 2300 CITY Denver STATE	CO <sub>ZIP</sub> 80290 PHONE NUMBER: (303) 837-1661	10. FIELD AND POOL, OR WLDCAT: Ashley Vally - Weber
4. LOCATION OF WELL	ZIP	
FOOTAGES AT SURFACE: 2665' FNL, 725' FWL	All Andrews Commencer	COUNTY: Uintah
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: NWSW 23	5S 22E	STATE: UTAH
11. CHECK APPROPRIATE BOXES TO	INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
NOTICE OF INTENT	DEEPEN	REPERFORATE CURRENT FORMATION
(Submit in Duplicate) ALTER CASING	FRACTURE TREAT	SIDETRACK TO REPAIR WELL
Approximate date work will start: CASING REPAIR	NEW CONSTRUCTION	TEMPORARILY ABANDON
CHANGE TO PREVIOUS PLA		TUBING REPAIR
CHANGE TUBING	PLUG AND ABANDON	VENT OR FLARE
SUBSEQUENT REPORT (Submit Original Form Only)	PLUG BACK	WATER DISPOSAL
Date of work completion:	PRODUCTION (START/RESUME)	☐ WATER SHUT-OFF
CONVERT WELL TYPE		OTHER:
CONVERT WELL TYPE	RECOMPLETE - DIFFERENT FORMATION	
On December 9 and 10, 2004 Whiting Oil and Gas indicated on the attached Job Log. Plugging work under the direction of Harlan Hodge. David Hackl Remaining work includes reseeding the surface as allows and a final sundry will be submitted after the	s Corp. plugged and abandoned the Ash k, including cementing, was subcontracte ford with the Utah DOGM was on site do nd removing deadmen. This work will be	ley Vally Fee #1 wellbore as and to Western Wellsite Services LLC uring plugging operations. a completed in the Spring as weather
NAME (PLEASE PRINT) Thomas B. Smith	TITLE Sr. Operations	Engineer
SIGNATURE Thrus Blant	DATE 1/11/2005	

(This space for State use only)

Edvic Hack Ford - State of what onsite

# **JOB LOG**

## WESTERN WELLSITE SERVICES LLC 17509 ROAD 14 FORT MORGAN, COLORADO 80701

OPERATOR	Whiting Petrolemm
WELL	Ashlen Vally# 1
LOCATION	NWSW 23 550 22E
DATE	12-10-04

DATE	12-10-0-	7
TIH/ 61/4 BIT	+ Sub	
	40'	
Cut Tubias OFFC	04010'	
SET 7" CICR @	<del></del>	
-0-INTENTION K		
STING OUT, SPUT	30 SKS ON TUI	
TUH TO 3200'		
MIX + Pump 40 SK	5 + WOC.	
RIH + TOG Plus CE		
/	00'	O Coli
• ————————————————————————————————————	SET@ 1069"	
MIX + Pump 60 Six.	5 50 UND-11.	SPUT IN ESTUP
TUH	~ <u></u>	The state of the s
Parf Well@ 556		11/2/2000
TIH + SET CICR C		· oftio
MIX + Pump 40 SHG	20 CLNDer	SPOT 10 ON TOP
TUH	<del></del>	
DIF OUT & CUT OFF Well Head		
1" TO 100' IN ANNULS + 7" Production Casing		
Weld au Plate/Logal Discription		
BACK FILL ARMY WELL BOX &		
ROMO		
WIRELINE CONTRACTOR		D. UTall
	Excell servi	Le Price UTalt
CEMENT CONTRACTOR	Western Wellsite Services of Ft. Morgan, Co.	
DIRTWORK CONTRACTOR	NA	
RESEEDING CONTRACTOR	JNA	
SIGNED:	Field Supervisor	DATE: 1-2-112-04

#### **First Commercial Production**

Ashley Valley Field

Equity #1, API: 43-047-15396

Year Discovered: September 14, 1948.

County: Uintah

Location: Section 23, Township 5 South, Range 22 East

Depth: 4,152 Feet

Producing Interval: Weber Formation 4,134 – 4,152 Openhole

In 1900 the first well in Uintah County, was drilled by John Pope in Section 35, Township 15 South, Range 23 East. It was 1,000 feet deep and had no shows of Oil or Gas. It would take another Forty-Eight years before the "First Commercially Productive Oil" well in Utah was drilled. It is located just 60 miles north of the John Pope well in Ashley Valley, and is the Equity #1, located, 2,665 FNL, 725 FWL, NE ¼ NW ¼ SW ¼, Section 23, Township 5 South, Range 22 East, Uintah County, Utah.

The well was completed on the 23<sup>rd</sup> day of September 1948 flowing 300 barrels of Oil a day from the Weber Formation.

Information Source: Drilling Records for Oil & Gas In Utah, George H. Hansen & H.C. Scoville, 1955, Pages 7, 12

James B. Larson P.E., Oil & Gas Fields of Utah, Geological Association Publication 22, 1933, Ashley Valley Field, Compiled by Bradley G. Hill, & S. Robert Bereskin

### First Permit Issued By Oil & Gas Commission

Wildcat Well

Sitton #4, API: 43-037-11440 Year Permitted: October 20, 1955.

County: San Juan

Location: Section 16, Township 33 South, Range 25 East

Depth: 6083 Feet

Information Source: Division of Oil, Gas & Mining Database,

Well file Division Public Information Room

### Number One Oil & Gas Producer

Anschutz Ranch East Field

Anschutz Ranch East, W29-06A, API: 43-043-30250

Year Completed: July 13, 1983.

County: Summit

Location: Section 29, Township 4 North, Range 8 East Depth: 14,390 Feet, BBLS 9,949,137, & MCF 28,418,865

Information Source: Division of Oil, Gas & Mining Production Database,

Well file Division Public Information Room